

Codice articolo

MFVN 10.32




Custodia mobile, serie LS-TYPE, con 4 piolini, ingresso cavo verticale M32 senza adattatore, grandezza "57.27", alta

Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Custodia mobile	Colore	Nero RAL 9005
Serie	LS-TYPE	Conformità RoHs	Conforme
Tipo chiusura	Con 4 piolini	China RoHs - EFUP	E
Grandezza	Grandezza "57.27"	Sostanze REACH SVHC	No
Ingresso cavo	Ingresso cavo verticale M32	Approvazioni / Normative	
Specifica	Alta	Certificazioni	DNV, BV
Dati tecnici		UL	ECBT2
Grado di protezione IP	IP65	cUL	ECBT8
Ulteriori dettagli tecnici		Informazioni commerciali	
Peso	167,50 g	Codice EAN13	8015747163583
Temperature di esercizio (min, max)	-40°C...+125°C	Classificazione ecl@ss	27440202
		Classificazione ETIM	EC000437
		Caratteristiche imballaggio	
		Lunghezza imballo	150,00 mm
		Altezza imballo	160,00 mm
		Profondità imballo	300,00 mm
		Peso imballo	3,35 kg
		Volume imballo	7,20 dm ³
		Descrizione imballo	Scatola cartone
		Quantità imballo	20 pz
		Codice EAN13 imballo	8015747187787
		Peso sottoimballo	0,84 kg
		Descrizione sottoimballo	Termoretraibile
		Quantità sottoimballo	5 pz
		Codice EAN13 sottoimballo	8015747187794

Codice articolo MFVN 10.32



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures size "57.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CDD	42 poles + ⊕ 61 *		
CQE	18 poles + ⊕ 81 *		
CSH	10 poles + ⊕ 89 *		
CCE	10 poles + ⊕ 90 *		
CNE, CSE, JONE, JCSE	10 poles + ⊕ 97 and 107 *		
CSS	10 poles + ⊕ 119 *		
CTE, CTSE **)	10 poles + ⊕ 127 *		
CMSE	3+2 (aux) poles + ⊕ 135 *		
CMCE	3+2 (aux) poles + ⊕ 134 *		
CX	8/24 poles + ⊕ 151 *		
MIXO	3 modules 160+195 *		

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

description	part no.		part no.	
	entry	M	entry	M
bulkhead mounting housing, with 2 levers	CHIN 10			
surface mounting housing, high construction, with 2 levers	MAPN 10.32 32			
with pegs, side entry			MHON 10.25 25	25
with pegs, side entry, high construction			MFON 10.32 32	32
with pegs, top entry			MHVN 10.25 25	25
with pegs, top entry, high construction			MFVN 10.32 32	32

**) only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

6

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.