

Codice articolo

MHON 24.32




Custodia mobile, serie LS-TYPE, con 4 piolini, ingresso cavo orizzontale M32, grandezza "104.27"

Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Custodia mobile	Colore	Nero RAL 9005
Serie	LS-TYPE	Conformità RoHs	Conforme
Tipo chiusura	Con 4 piolini	China RoHs - EFUP	E
Grandezza	Grandezza 104.27	Sostanze REACH SVHC	No
Ingresso cavo	Ingresso cavo orizzontale M32	Approvazioni / Normative	
Dati tecnici		Certificazioni	DNV, BV
Grado di protezione IP	IP65	UL	ECBT2
Ulteriori dettagli tecnici		cUL	ECBT8
Peso	197,00 g	Informazioni commerciali	
Temperature di esercizio (min, max)	-40°C...+125°C	Codice EAN13	8015747194303
		Classificazione ecl@ss	27440202
		Classificazione ETIM	EC000437
		Caratteristiche imballaggio	
		Peso sottoimballo	0,99 kg
		Descrizione sottoimballo	Termoretraibile
		Quantità sottoimballo	5 pz
		Codice EAN13 sottoimballo	8015747194310

Codice articolo MHON 24.32



Disegni da catalogo



Disegni da catalogo

CH..N - MA, MF..N enclosures size "104.27" **LS-TYPE version**

inserts: page

CD	64 poles + Ⓞ	51+53 *
CT, CTS **)	64 poles + Ⓞ	57 *
CDD	108 poles + Ⓞ	64+66 *
CDE	46 poles + Ⓞ	83+85 *
CSH	24 poles + Ⓞ	91+93 *
CCE	24 poles + Ⓞ	100+104 *
CNE, CSE, JCNE, JCSE	24 poles + Ⓞ	101 and 109 *
CSS	24 poles + Ⓞ	122+123 *
CTE, CTSE **)	24 poles + Ⓞ	129 *
CMSE	10+2 (aux)	139 *
CMCE	10+2 (aux)	138 *
CX	4/8 poles + Ⓞ	155 *
MIXO	6 modules	160+195 *

insert centre distance: 104 x 27 mm
* refer to catalogue page CN.12

description	part no.		entry	
			M	
bulkhead mounting housing, with 2 levers	CHIN 24			
surface mounting housing, high construction, with 2 levers	MAPN 24.32	32		
with pegs, side entry				MHON 24.32 32
with pegs, side entry, high construction				MFON 24.32 32
with pegs, side entry				MHVN 24.32 32
with pegs, side entry, high construction				MFVN 24.32 32

**) only in the CHIN 24 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

CHIN 24		MFON 24.32	
MAPN 24.32		MFVN 24.32	
		MHON 24.32	
		MHVN 24.32	

10

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.