

Codice articolo

# MHVN 06 L25




Custodia mobile, serie LS-TYPE, con 2 piolini, ingresso cavo verticale M25, grandezza "44.27"

Descrizione prodotto		Proprietà dei materiali	
<b>Tipo prodotto</b>	Custodia mobile	<b>Colore</b>	Nero RAL 9005
<b>Serie</b>	LS-TYPE	<b>Conformità RoHs</b>	Conforme
<b>Tipo chiusura</b>	Con 2 piolini	<b>China RoHs - EFUP</b>	E
<b>Grandezza</b>	Grandezza "44.27"	<b>Sostanze REACH SVHC</b>	No
<b>Ingresso cavo</b>	Ingresso cavo verticale M25	Approvazioni / Normative	
Dati tecnici		<b>Certificazioni</b>	DNV, BV
<b>Grado di protezione IP</b>	IP65	<b>UL</b>	ECBT2
Ulteriori dettagli tecnici		<b>cUL</b>	ECBT8
<b>Peso</b>	84,00 g	Informazioni commerciali	
<b>Temperature di esercizio (min, max)</b>	-40°C...+125°C	<b>Codice EAN13</b>	8015747194204
		<b>Classificazione ecl@ss</b>	27440202
		<b>Classificazione ETIM</b>	EC000437
		Caratteristiche imballaggio	
		<b>Peso sottoimballo</b>	0,42 kg
		<b>Descrizione sottoimballo</b>	Termoretraibile
		<b>Quantità sottoimballo</b>	5 pz
		<b>Codice EAN13 sottoimballo</b>	8015747123341

# Codice articolo MHVN 06 L25



Disegni da catalogo



Disegni da catalogo

**CH..N - MA, MF..N enclosures** size "44.27" **LS-TYPE version**

inserts:	page	housings with single lever	hoods with 2 pegs
CDD .....	24 poles + ⊕ 59 *		
CQE .....	10 poles + ⊕ 80 *		
CSH .....	6 poles + ⊕ 88 *		
CCE .....	6 poles + ⊕ 94 *		
CNE, CSE, JONE, JOSE .....	6 poles + ⊕ 95 and 103 *		
CSS .....	6 poles + ⊕ 118 *		
CTE, CTSE **) .....	6 poles + ⊕ 126 *		
MIXO .....	2 modules 160+195 *		

insert centre distance: 44 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with lever	CHIN 06 L	M		
surface mounting housing, high construction, with lever	MAPN 06 L32	32		
with pegs, side entry			MHON 06 L25	25
with pegs, side entry, high construction			MFON 06 L25	25
with pegs, top entry			MHVN 06 L25	25
with pegs, top entry, high construction			MFVN 06 L25	25

\*\*) only in the CHIN 06 L enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

IP65

dimensions shown are not binding and may be changed without notice

4

## Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.