


Codice articolo

TM 32123KIS



Presa con interruttore di blocco, serie TM, 2 poli + PE, 12 h (bianco), 32 A, portafusibile sezionabile 10 x 38 mm, con scatola base

Descrizione prodotto	
Tipo prodotto	Preso con interruttore di blocco
Serie	TM.. IS/KIS
N. poli	2 poli + 
Riferimento orario	12
Specifica	Portafusibile sezionabile 10 x 38 mm Con scatola base
Dati tecnici	
Corrente	32 A
Tensione	Trasformatore isol.
Grado di protezione IP	IP66 / IP67
Ulteriori dettagli tecnici	
Temperature di esercizio (min, max)	-25°C ... +40°C
Grado autoestinguenza UL 94	V-2
Grado di protezione IK (urti)	IK10

Proprietà dei materiali	
Colore	Grigio RAL 7012, bianco RAL 9010
Approvazioni / Normative	
Normativa di riferimento	EN 60309-1, -2 e -4
Informazioni commerciali	
Codice EAN13	8015747162173

Codice articolo TM 32123KIS



Disegni da catalogo

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with I_{BT}= 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

16A
IP66/IP67 degree of protection

32A
IP66/IP67 degree of protection

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+Ⓢ	50 and 60	100 - 130	4	TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow	
		200 - 250	6	TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue	
	50 and 60	380 - 415	9	TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red	
		480 - 500	7	TM 1673 IS Ⓢ	Black	TM 3273KIS Ⓢ	Black	
	50 and 60	ins. transformer	12	TM 16123 IS Ⓢ	A.V.	TM 32123KIS Ⓢ	A.V.	
			2	TM 1623 IS Ⓢ	+	TM 3223KIS Ⓢ (up to 400V)	+	
	> 300 - 500	> 50 - 250	3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
			3					
	3P+Ⓢ	50 and 60	100 - 130	4	TM 1644 IS Ⓢ	Yellow	TM 3244KIS Ⓢ	Yellow
			200 - 250	9	TM 1694 IS Ⓢ	Red	TM 3294KIS Ⓢ	Red
50 and 60		380 - 415	6	TM 1664 IS Ⓢ	Blue	TM 3264KIS Ⓢ	Blue	
		440 - 460	11	TM 16114 IS Ⓢ	Black	TM 32114KIS Ⓢ	Black	
50 and 60		480 - 500	7	TM 1674 IS Ⓢ	Black	TM 3274KIS Ⓢ	Black	
			3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
60		440	3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
			10	TM 16104 IS Ⓢ	+	TM 32104KIS Ⓢ (up to 400V)	+	
> 300 - 500		> 50	2	TM 1624 IS Ⓢ	+	TM 3224KIS Ⓢ (up to 400V)	+	
			2					
3P+N+Ⓢ	50 and 60	57/100 - 75/130	4	TM 1645 IS Ⓢ	Yellow	TM 3245KIS Ⓢ	Yellow	
		120/208 - 144/250	9	TM 1695 IS Ⓢ	Red	TM 3295KIS Ⓢ	Red	
	50 and 60	200/346 - 240/415	6	TM 1665 IS Ⓢ	Blue	TM 3265KIS Ⓢ	Blue	
			7	TM 1675 IS Ⓢ	Black	TM 3275KIS Ⓢ	Black	
	50 and 60	277/480 - 288/500	11	TM 16115 IS Ⓢ	Black	TM 32115KIS Ⓢ	Black	
			3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
	60	250/440 - 265/460	3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
			6	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
	> 300 - 500	> 50	2	TM 1625 IS Ⓢ	+	TM 3225KIS Ⓢ (up to 400V)	+	
			2					

Legend
A.V. = Colour according to voltage
*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

Accessories for socket-outlet combinations

Accessories for assembly on control panels
QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

Poles	A	B
2P+Ⓢ	133	276
3P+Ⓢ	135	276
3P+N+Ⓢ	140	277

12

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.