


Codice articolo

# TM 3224KIS



Presa con interruttore di blocco, serie TM, 3 poli + PE, 2 h (verde), 32 A, > 50 V, portafusibile sezionabile 10 x 38 mm, con scatola base

#### Descrizione prodotto

<b>Tipo prodotto</b>	Preso con interruttore di blocco
<b>Serie</b>	TM.. IS/KIS
<b>N. poli</b>	3 poli + 
<b>Riferimento orario</b>	2
<b>Specifica</b>	Portafusibile sezionabile 10 x 38 mm Con scatola base

#### Dati tecnici

<b>Corrente</b>	32 A
<b>Tensione</b>	> 50 V
<b>Grado di protezione IP</b>	IP66 / IP67

#### Ulteriori dettagli tecnici

<b>Temperature di esercizio (min, max)</b>	-25°C ... +40°C
<b>Grado autoestinguenza UL 94</b>	V-2
<b>Grado di protezione IK (urti)</b>	IK10

#### Proprietà dei materiali

<b>Colore</b>	Grigio RAL 7012, verde RAL 6017
---------------	---------------------------------

#### Approvazioni / Normative

<b>Normativa di riferimento</b>	EN 60309-1, -2 e -4
---------------------------------	---------------------

#### Informazioni commerciali

<b>Codice EAN13</b>	8015747162432
---------------------	---------------

# Codice articolo TM 3224KIS



Disegni da catalogo

### TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with  $I_{n1} = 32A$  rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

**16A**  
IP66/IP67 degree of protection

**32A**  
IP66/IP67 degree of protection

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+Ⓢ	50 and 60	100 - 130	4	TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow	
		200 - 250	6	TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue	
	50 and 60	380 - 415	9	TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red	
		480 - 500	7	TM 1673 IS Ⓢ	Black	TM 3273KIS Ⓢ	Black	
	50 and 60	ins. transformer	12	TM 16123 IS Ⓢ	A.V.	TM 32123KIS Ⓢ	A.V.	
			2	TM 1623 IS Ⓢ	+	TM 3223KIS Ⓢ (up to 400V)	+	
	> 300 - 500	> 50 - 250	3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
			3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
	3P+Ⓢ	50 and 60	100 - 130	4	TM 1644 IS Ⓢ	Yellow	TM 3244KIS Ⓢ	Yellow
			200 - 250	9	TM 1694 IS Ⓢ	Blue	TM 3294KIS Ⓢ	Blue
50 and 60		380 - 415	6	TM 1664 IS Ⓢ	Red	TM 3264KIS Ⓢ	Red	
		440 - 460	11	TM 16114 IS Ⓢ	Black	TM 32114KIS Ⓢ	Black	
50 and 60		480 - 500	7	TM 1674 IS Ⓢ	Black	TM 3274KIS Ⓢ	Black	
			3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
60		440	3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black	
			10	TM 16104 IS Ⓢ	+	TM 32104KIS Ⓢ (up to 400V)	+	
> 300 - 500		> 50	2	TM 1624 IS Ⓢ	+	TM 3224KIS Ⓢ (up to 400V)	+	
			2	TM 1624 IS Ⓢ	+	TM 3224KIS Ⓢ (up to 400V)	+	
3P+N+Ⓢ	50 and 60	57/100 - 75/130	4	TM 1645 IS Ⓢ	Yellow	TM 3245KIS Ⓢ	Yellow	
		120/208 - 144/250	9	TM 1695 IS Ⓢ	Blue	TM 3295KIS Ⓢ	Blue	
	50 and 60	200/346 - 240/415	6	TM 1665 IS Ⓢ	Red	TM 3265KIS Ⓢ	Red	
			7	TM 1675 IS Ⓢ	Black	TM 3275KIS Ⓢ	Black	
	50 and 60	277/480 - 288/500	11	TM 16115 IS Ⓢ	Black	TM 32115KIS Ⓢ	Black	
			3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
	60	250/440 - 265/460	3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
			6	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
	> 300 - 500	> 50	3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black	
			2	TM 1625 IS Ⓢ	+	TM 3225KIS Ⓢ (up to 400V)	+	

**Legend**  
A.V. = Colour according to voltage  
\*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

**Accessories for socket-outlet combinations**

TM 1145 TB (page 24) with 1 plate  
TM 1114 DB (page 26) with 2 plates  
TM 1114 GB (page 27)

**Accessories for assembly on control panels**

QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

**Dimensions in mm**

Poles	A	B
2P+Ⓢ	133	276
3P+Ⓢ	135	276
3P+N+Ⓢ	140	277

Poles	A
2P+Ⓢ	146
3P+Ⓢ	146
3P+N+Ⓢ	151

## Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.