

Codice articolo

TM 3244KIS



Presa con interruttore di blocco, serie TM, 3 poli + PE, 4 h (giallo), 32 A, 100 ÷ 130 V, portafusibile sezionabile 10 x 38 mm, con scatola base

Descrizione prodotto	
Tipo prodotto	Preso con interruttore di blocco
Serie	TM.. IS/KIS
N. poli	3 poli + 
Riferimento orario	4
Grandezza	115 x 450 x 18 mm
Specifica	Portafusibile sezionabile 10 x 38 mm Con scatola base
Dati tecnici	
Corrente	32 A
Tensione	100 ÷ 130 V
Grado di protezione IP	IP66 / IP67
Ulteriori dettagli tecnici	
Peso	1.660,00 g
Temperature di esercizio (min, max)	-25°C ... +40°C
Grado autoestinguenza UL 94	V-2
Grado di protezione IK (urti)	IK10

Proprietà dei materiali	
Colore	Grigio RAL 7012, giallo RAL 1021
Approvazioni / Normative	
Normativa di riferimento	EN 60309-1, -2 e -4
Informazioni commerciali	
Codice EAN13	8015747126496



TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier



- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zetta" switch with I_{n1} 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions O and I
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

Poles	Frequency Hz	Voltage V	Earthing contact position h
2P+@	50 and 60	100 - 130	4
	50 and 60	200 - 250	6
	50 and 60	380 - 415	9
	50 and 60	480 - 500	7
	50 and 60	ins. transformer	12
	> 300 - 500 d.c.	> 50	2
	> 50 - 250	> 50	3
3P+@	50 and 60	100 - 130	4
	50 and 60	200 - 250	9
	50 and 60	380 - 415	6
	60	440 - 460	11
	50 and 60	480 - 500	7
	50	380	3
	60	440	3
3P+N+@	50 and 60	57/100 - 75/130	4
	50 and 60	120/208 - 144/250	9
	50 and 60	200/346 - 240/415	6
	50 and 60	277/480 - 288/500	7
	60	250/440 - 265/460	11
	50	220/380	3
	60	250/440	3

16A
IP66/IP67 degree of protection



Part No.	Colour
TM 1643 IS @	Yellow
TM 1663 IS @	Blue
TM 1693 IS @	Red
TM 1673 IS @	Black
TM 16123 IS @	A.V.
TM 1623 IS @	A.V.
TM 1633 IS @	A.V.
TM 1644 IS @	Yellow
TM 1694 IS @	Blue
TM 1664 IS @	Red
TM 16114 IS @	Black
TM 1674 IS @	Black
TM 1634 IS @	Black
TM 1634 IS @	Black
TM 16104 IS @	*)
TM 1624 IS @	*)
TM 1645 IS @	Yellow
TM 1695 IS @	Blue
TM 1665 IS @	Red
TM 1675 IS @	Black
TM 16115 IS @	Black
TM 1635 IS @	Black
TM 1635 IS @	Black
TM 1625 IS @	*)


32A
IP66/IP67 degree of protection




Part No.	Colour
TM 3243KIS @	Yellow
TM 3263KIS @	Blue
TM 3293KIS @	Red
TM 32123KIS @	A.V.
TM 3223KIS @ (up to 400V)	A.V.
TM 3233KIS @	A.V.
TM 3244KIS @	Yellow
TM 3294KIS @	Blue
TM 3264KIS @	Red
TM 3234KIS @	Black
TM 32104KIS @ (up to 400V)	*)
TM 3224KIS @ (up to 400V)	*)
TM 3245KIS @	Yellow
TM 3295KIS @	Blue
TM 3265KIS @	Red
TM 3235KIS @	Black
TM 3225KIS @ (up to 400V)	*)

Legend


A.V. = Colour according to voltage
*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz



dimensions in mm



dimensions in mm



Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.