


Codice articolo

TM 3245KIS



Presa con interruttore di blocco, serie TM, 3 poli + N + PE, 4 h (giallo), 32 A, 57/100 ÷ 75/130 V, portafusibile sezionabile 10 x 38 mm, con scatola base

Descrizione prodotto		Proprietà dei materiali	
Tipo prodotto	Presca con interruttore di blocco	Colore	Grigio RAL 7012, giallo RAL 1021
Serie	TM.. IS/KIS		Conforme con esenzioni
N. poli	3 poli + neutro + 	Conformità RoHs	6(c): lega di rame contenente fino al 4% in peso di piombo
Riferimento orario	4	China RoHs - EFUP	50
Grandezza	115 x 450 x 18 mm	Sostanze REACH SVHC	Si Piombo
Specifica	Portafusibile sezionabile 10 x 38 mm Con scatola base	Codice SCIP	Ce861c8d-b979-403b-96d9-80aef6dc281d
Dati tecnici		Approvazioni / Normative	
Corrente	32 A	Normativa di riferimento	EN 60309-1, -2 e -4
Tensione	57/100 ÷ 75/130 V	Informazioni commerciali	
Grado di protezione IP	IP66 / IP67	Codice EAN13	8015747126564
Ulteriori dettagli tecnici		Caratteristiche imballaggio	
Peso	1.695,00 g	Lunghezza imballo	385,00 mm
Temperature di esercizio (min, max)	-25°C ... +40°C	Altezza imballo	320,00 mm
Grado autoestinguenza UL 94	V-2	Profondità imballo	485,00 mm
Grado di protezione IK (urti)	IK10	Peso imballo	15,81 kg
		Volume imballo	59,75 dm ³
		Descrizione imballo	Scatola cartone
		Quantità imballo	9 pz
		Codice EAN13 imballo	8015747202411
		Peso sottoimballo	1,76 kg
		Descrizione sottoimballo	Termoretraibile
		Quantità sottoimballo	1 pz
		Codice EAN13 sottoimballo	8015747202428

Codice articolo TM 3245KIS



Disegni da catalogo

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (K 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with I_n= 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions 0 and 1
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

16A
IP66/IP67 degree of protection

32A
IP66/IP67 degree of protection

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+Ⓢ	50 and 60	100 - 130	4	TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow	
	50 and 60	200 - 250	6	TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue	
	50 and 60	380 - 415	9	TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red	
	50 and 60	480 - 500	7	TM 1673 IS Ⓢ	Black	TM 3273KIS Ⓢ	Black	
	50 and 60	ins. transformer	12	TM 16123 IS Ⓢ	A.V.	TM 32123KIS Ⓢ	A.V.	
	> 300 - 500	> 50	2	TM 1623 IS Ⓢ	Green	TM 3223KIS Ⓢ (up to 400V)	Green	
	d.c.	> 50 - 250	3	TM 1633 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.	
	3P+Ⓢ	50 and 60	100 - 130	4	TM 1644 IS Ⓢ	Yellow	TM 3244KIS Ⓢ	Yellow
		50 and 60	200 - 250	9	TM 1694 IS Ⓢ	Blue	TM 3294KIS Ⓢ	Blue
		50 and 60	380 - 415	6	TM 1664 IS Ⓢ	Red	TM 3264KIS Ⓢ	Red
60		440 - 460	11	TM 16114 IS Ⓢ	Black	TM 32114KIS Ⓢ	Black	
50 and 60		480 - 500	7	TM 1674 IS Ⓢ	Black	TM 3274KIS Ⓢ	Black	
50		380	3	TM 1634 IS Ⓢ	Red	TM 3234KIS Ⓢ	Red	
60		440	3	TM 1634 IS Ⓢ	Red	TM 3234KIS Ⓢ	Red	
100 - 300		> 50	10	TM 16104 IS Ⓢ	Green	TM 32104KIS Ⓢ (up to 400V)	Green	
> 300 - 500		> 50	2	TM 1624 IS Ⓢ	Green	TM 3224KIS Ⓢ (up to 400V)	Green	
3P+N+Ⓢ		50 and 60	57/100 - 75/130	4	TM 1645 IS Ⓢ	Yellow	TM 3245KIS Ⓢ	Yellow
	50 and 60	120/208 - 144/250	9	TM 1695 IS Ⓢ	Blue	TM 3295KIS Ⓢ	Blue	
	50 and 60	200/346 - 240/415	6	TM 1665 IS Ⓢ	Red	TM 3265KIS Ⓢ	Red	
	50 and 60	277/480 - 288/500	7	TM 1675 IS Ⓢ	Black	TM 3275KIS Ⓢ	Black	
	60	250/440 - 265/460	11	TM 16115 IS Ⓢ	Black	TM 32115KIS Ⓢ	Black	
	50	220/380	3	TM 1635 IS Ⓢ	Red	TM 3235KIS Ⓢ	Red	
	60	250/440	3	TM 1635 IS Ⓢ	Red	TM 3235KIS Ⓢ	Red	
	> 300 - 500	> 50	2	TM 1625 IS Ⓢ	Green	TM 3225KIS Ⓢ (up to 400V)	Green	

Legend
A.V. = Colour according to voltage
*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

Accessories for socket-outlet combinations

TM 1145 TB (page 24) with 1 plate
TM 1114 DB (page 26) with 2 plates
TM 1114 GB (page 27)

Accessories for assembly on control panels

QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

Dimensions in mm

Center for hole

255
114
A
B

Center for hole

255
114
A
B

Poles	A	B
2P+Ⓢ	133	276
3P+Ⓢ	135	276
3P+N+Ⓢ	140	277

Poles	A
2P+Ⓢ	146
3P+Ⓢ	146
3P+N+Ⓢ	151

Note

Le misure indicate non sono impegnative e possono essere variate senza alcun preavviso.