

品番

# CKSM 04



オス インサート, CKS シリーズ, バネ式結線, 4極 + PE, 10 A 400 V 4 kV 3, サイズ "21.21"

製品説明	
製品タイプ	インサート
シリーズ	CKS
接続タイプ	バネ式接続
性別	オス
極数	4極+
サイズ	サイズ"21.21"
技術データ	
電流	10 A
電圧	400 V
定格インパルス耐電圧	4 kV
汚染度	3
導体断面積	0,14 mm <sup>2</sup> - 2,50 mm <sup>2</sup>
AWG サイズ	26 - 14
コンタクトタイプ	切削コンタクト 銀メッキ
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ有りの場合IP44/IP66/IP67/IP68/IP69
技術詳細	
重さ	14,80 g
動作温度範囲 (最小 最大)	-40 °C ... +125 °C



材料特性	
主な素材	ポリカーボネート
その他の素材	銅合金 NBR
カラー	RAL 7032
SCIP番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
参照	EN 61984:2009-06
認証	CSA, CQC, DNV, BV, EAC
UL	ECBT2
cUL	ECBT8
ジェネラルオーダーリングインフォメーション	
EAN13 コード	8015747164382
パッケージ情報	
パッケージ長さ	210,00 mm
パッケージ高さ	200,00 mm
パッケージ幅	130,00 mm
パッケージ重量	3,06 kg
パッケージ体積	5,46 dm <sup>3</sup>
パッケージ 詳細	カートンボックス
パッケージ 数量	200 個
パッケージ  EAN コード	8015747164436
サブパッケージ 長さ	197,00 mm
サブパッケージ 高さ	35,00 mm
サブパッケージ 幅	124,00 mm
サブパッケージ 重量	0,61 kg
サブパッケージ 体積	0,85 dm <sup>3</sup>
サブパッケージ 詳細	カートントレイ
サブパッケージ 数量	40 個
サブパッケージ  EAN バーコード	8015747164443

品番


# CKSM 04



カタログ図面



カタログ図面



## メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。

### California Proposition 65 Information



**WARNING**

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

## California Proposition 65 Information



### WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).

---