

品番

CSEM 24 N



オス インサート, CSE シリーズ, バネ式結線, 24
極 + PE (25-48), 16 A 500 V 6 kV 3, サイズ
"104.62"

製品説明	
製品タイプ	インサート
シリーズ	CSE
接続タイプ	バネ式接続
性別	オス
極数	48極 +
サイズ	サイズ104.62
技術データ	
電流	16 A
電圧	500 V
定格インパルス耐電圧	6 kV
汚染度	3
導体断面積	0,14 mm ² - 2,50 mm ²
AWG サイズ	26 - 14
コンタクトタイプ	切削コンタクト 銀メッキ
極番号システム	25-48
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ 有りの場合IP65/IP66
技術詳細	
重さ	113,00 g
動作温度範囲 (最小 最大)	-40 °C ... +125 °C

材料特性	
主な素材	ポリカーボネート
カラー	RAL 7032
SCIP番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
参照	EN 61984:2009-06
認証	CSA, CQC, DNV, BV, EAC
UL	ECBT2
ジェネラルオーダリングインフォメーション	
EAN13 コード	8015747094726
パッケージ情報	
パッケージ長さ	270,00 mm
パッケージ高さ	75,00 mm
パッケージ幅	180,00 mm
パッケージ重量	3,73 kg
パッケージ体積	3,65 dm ³
パッケージ 詳細	カートンボックス
パッケージ 数量	30 個
パッケージ EAN コード	8015747094733
サブパッケージ 長さ	113,00 mm
サブパッケージ 高さ	36,00 mm
サブパッケージ 幅	180,00 mm
サブパッケージ 重量	0,62 kg
サブパッケージ 体積	0,73 dm ³
サブパッケージ 詳細	カートントレイ
サブパッケージ 数量	5 個
サブパッケージ EAN バーコード	8015747094740



品番

CSEM 24 N



カタログ図面

カタログ図面




CSEF 24 N

CSEF 24

CSEM 24

CSEM 24 N



メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.
