


品番

CTS F 40 L



メス インサート, CTS シリーズ, バネ式結線, 40 極 + PE, 10 A 250 V 4 kV 3, サイズ "77.27", 端子台付き, 左側面取付

製品説明	
製品タイプ	インサート
シリーズ	CTS
接続タイプ	バネ式接続
性別	メス
極数	40極 +
サイズ	サイズ"77.27"
仕様	側面取付(左) 端子台付
技術データ	
電流	10 A
電圧	250 V
定格インパルス耐電圧	4 kV
汚染度	3
導体断面積	0,14 mm ² - 2,50 mm ²
AWG サイズ	26 - 14
コンタクトタイプ	切削コンタクト 銀メッキ
IP 保護等級	エンクロージャなしの場合IP20 エンクロージャ 有りの場合IP66/IP69
技術詳細	
重さ	330,00 g
動作温度範囲 (最小 最大)	-40 °C ... +125 °C


材料特性	
主な素材	ポリカーボネート
その他の素材	銅合金
カラー	RAL 7032
SCIP 番号	1a9c93ff-0445-4a16-81e3-1609ac5274d6
認証 / 規格	
参照	EN 61984:2009-06
認証	CSAc, CQC, DNV, BV, EAC
UL	ECBT2
ジェネラルオーダリングインフォメーション	
EAN13 コード	8015747041485
ecl@ss 分類	27440205
ETIM 分類	EC000438
パッケージ情報	
パッケージ長さ	160,00 mm
パッケージ高さ	115,00 mm
パッケージ幅	137,00 mm
パッケージ重量	0,75 kg
パッケージ体積	2,52 dm ³
パッケージ 詳細	カートンボックス
パッケージ 数量	2個
パッケージ EAN コード	8015747260510
サブパッケージ 重量	0,38 kg
サブパッケージ 詳細	プラスチック包装
サブパッケージ 数量	1個
サブパッケージ EAN バーコード	8015747041492

品番



CTSF 40 L



カタログ図面



カタログ図面



メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.

California Proposition 65 Information



WARNING

This product can expose you to lead and its compounds, known to the State of California to cause cancer and/or reproductive toxicity. For more information go to www.P65Warnings.ca.gov.