

品番

TM 3243KIS



製品説明

製品タイプ	2K
シリーズ	2TIS
極数	2極 + 
時計位置	4
サイズ	115x450
仕様	2F10 2CS

技術データ

電流	32 A
電圧	100 - 130 V
IP 保護等級	IP66 / IP67

技術詳細

重さ	1.540,00 g
----	------------

材料特性

カラー	RAL 7012
-----	----------

認証 / 規格

参照	EN 60309-1, -2 e -4
----	---------------------

ジェネラルオーダーリングインフォメーション

EAN13 コード	8015747126441
-----------	---------------

カタログ図面

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier



- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with I_{n1} 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions O and I
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

Poles	Frequency Hz	Voltage V	Earthing contact position h
2P+Ⓢ	50 and 60	100 - 130	4
	50 and 60	200 - 250	6
	50 and 60	380 - 415	9
	50 and 60	480 - 500	7
	50 and 60	ins. transformer	12
	> 300 - 500	> 50	2
	d.c.	> 50 - 250	3
3P+Ⓢ	50 and 60	100 - 130	4
	50 and 60	200 - 250	9
	50 and 60	380 - 415	6
	60	440 - 460	11
	50 and 60	480 - 500	7
	50	380	3
	60	440	3
3P+N+Ⓢ	50 and 60	57/100 - 75/130	4
	50 and 60	120/208 - 144/250	9
	50 and 60	200/346 - 240/415	6
	50 and 60	277/480 - 288/500	7
	60	250/440 - 265/460	11
	50	220/380	3
	60	250/440	3


16A
IP66/IP67 degree of protection32A
IP66/IP67 degree of protection

Part No.	Colour	Part No.	Colour
TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow
TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue
TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red
TM 1673 IS Ⓢ	Black	TM 32123KIS Ⓢ	A.V.
TM 16123 IS Ⓢ	A.V.	TM 3223KIS Ⓢ (up to 400V)	A.V.
TM 1623 IS Ⓢ	A.V.	TM 3233KIS Ⓢ	A.V.
TM 1633 IS Ⓢ	A.V.	TM 3244KIS Ⓢ	Yellow
TM 1644 IS Ⓢ	Yellow	TM 3294KIS Ⓢ	Red
TM 1694 IS Ⓢ	Red	TM 3264KIS Ⓢ	Blue
TM 1664 IS Ⓢ	Blue	TM 3234KIS Ⓢ	Black
TM 16114 IS Ⓢ	Black	TM 32104KIS Ⓢ (up to 400V)	A.V.
TM 1674 IS Ⓢ	Black	TM 3224KIS Ⓢ (up to 400V)	A.V.
TM 1634 IS Ⓢ	Black	TM 3245KIS Ⓢ	Yellow
TM 1634 IS Ⓢ	Black	TM 3295KIS Ⓢ	Red
TM 16104 IS Ⓢ	A.V.	TM 3265KIS Ⓢ	Blue
TM 1624 IS Ⓢ	A.V.	TM 3235KIS Ⓢ	Black
TM 1645 IS Ⓢ	Yellow	TM 3225KIS Ⓢ (up to 400V)	A.V.
TM 1695 IS Ⓢ	Red		
TM 1665 IS Ⓢ	Blue		
TM 1675 IS Ⓢ	Black		
TM 16115 IS Ⓢ	Black		
TM 1635 IS Ⓢ	Black		
TM 1635 IS Ⓢ	Black		
TM 1625 IS Ⓢ	A.V.		

Legend

A.V. = Colour according to voltage

*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz



Accessories for assembly on control panels


QP V - QG V




page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm



dimensions in mm



mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。