


品番

TM 3244KIS



製品説明

製品タイプ	2K
シリーズ	2TIS
極数	3極 + 
時計位置	4
サイズ	115x450
仕様	2F10 2CS

技術データ

電流	32 A
電圧	100 - 130 V
IP 保護等級	IP66 / IP67

技術詳細

重さ	1.660,00 g
----	------------

材料特性

カラー	RAL 7012
-----	----------

認証 / 規格

参照	EN 60309-1, -2 e -4
----	---------------------

ジェネラルオーダリングインフォメーション

EAN13 コード	8015747126496
-----------	---------------



カタログ図面

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with I_{n1} = 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions O and I
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour	
2P+⊕	50 and 60	100 - 130	4	TM 1643 IS ⊕	Yellow	TM 3243KIS ⊕	Yellow	
		200 - 250	6	TM 1663 IS ⊕	Blue	TM 3263KIS ⊕	Blue	
		380 - 415	9	TM 1693 IS ⊕	Red	TM 3293KIS ⊕	Red	
		480 - 500	7	TM 1673 IS ⊕	Black	TM 3273KIS ⊕	Black	
		ins. transformer	12	TM 16123 IS ⊕	A.V.	TM 32123KIS ⊕	A.V.	
		> 300 - 500	> 50	2	TM 1623 IS ⊕	Green	TM 3223KIS ⊕ (up to 400V)	Green
3P+⊕	50 and 60	100 - 130	4	TM 1644 IS ⊕	Yellow	TM 3244KIS ⊕	Yellow	
		200 - 250	9	TM 1694 IS ⊕	Red	TM 3294KIS ⊕	Red	
		380 - 415	6	TM 1664 IS ⊕	Blue	TM 3264KIS ⊕	Blue	
		440 - 460	11	TM 16114 IS ⊕	Black	TM 32114KIS ⊕	Black	
		480 - 500	7	TM 1674 IS ⊕	Black	TM 3274KIS ⊕	Black	
		380	3	TM 1634 IS ⊕	Black	TM 3234KIS ⊕	Black	
		440	3	TM 1634 IS ⊕	Black	TM 3234KIS ⊕	Black	
		100 - 300	> 50	10	TM 16104 IS ⊕	Green	TM 32104KIS ⊕ (up to 400V)	Green
		> 50 - 250	3	TM 1633 IS ⊕	Black	TM 3233KIS ⊕	Black	
		> 300 - 500	> 50	2	TM 1624 IS ⊕	Green	TM 3224KIS ⊕ (up to 400V)	Green
3P+N+⊕	50 and 60	57/100 - 75/130	4	TM 1645 IS ⊕	Yellow	TM 3245KIS ⊕	Yellow	
		120/208 - 144/250	9	TM 1695 IS ⊕	Red	TM 3295KIS ⊕	Red	
		200/346 - 240/415	6	TM 1665 IS ⊕	Blue	TM 3265KIS ⊕	Blue	
		277/480 - 288/500	7	TM 1675 IS ⊕	Black	TM 3275KIS ⊕	Black	
		250/440 - 265/460	11	TM 16115 IS ⊕	Black	TM 32115KIS ⊕	Black	
		220/380	3	TM 1635 IS ⊕	Black	TM 3235KIS ⊕	Black	
		250/440	3	TM 1635 IS ⊕	Black	TM 3235KIS ⊕	Black	
		> 300 - 500	> 50	2	TM 1625 IS ⊕	Green	TM 3225KIS ⊕ (up to 400V)	Green

Legend
 A.V. = Colour according to voltage
 *) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

Accessories for socket-outlet combinations

TM 1145 TB (page 24) with 1 plate
 TM 1114 DB (page 26) with 2 plates
 TM 1114 GB (page 27)

Accessories for assembly on control panels

QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

Poles	A	B
2P+⊕	133	276
3P+⊕	135	276
3P+N+⊕	140	277

dimensions in mm

Poles	A
2P+⊕	146
3P+⊕	146
3P+N+⊕	151

メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。