


品番

TM 3295KIS



製品説明

製品タイプ	2K
シリーズ	2TIS
極数	3極 + N + 
時計位置	9
サイズ	115x450
仕様	2F10 2CS

技術データ

電流	32 A
電圧	208 - 250 V
IP 保護等級	IP66 / IP67

技術詳細

重さ	1.750,00 g
----	------------

材料特性

カラー	RAL 7035
-----	----------

認証 / 規格

参照	EN 60309-1, -2 e -4
----	---------------------

ジェネラルオーダーリングインフォメーション

EAN13 コード	8015747126328
-----------	---------------



カタログ図面

TM.. IS/KIS interlocked socket-outlets and sectionable fuse carrier

- Compliant with EN 60309 -1, -2 and 4
- Enclosures in insulating self-extinguishing thermoplastic material, RAL 7012 grey
- Mechanical resistance to impacts: 20 J (IK 10 as EN 50102)
- Socket-outlets with bayonet fastening cover
- Factory installed internal wiring
- Cable entry with drilling template
- "Zeta" switch with I_{n1} = 32A rating for 16A and 32A socket-outlets
- Mechanical interlock that prevents: the switch from being turned on without the plug inserted and the plug from being removed while the switch is on
- Knob lockable in positions O and I
- Compartment with sectionable fuse carrier (fuses not supplied) and inspection panel openable only when the switch is off
- With Italian Quality Mark

Rated current socket part	Maximum operating current	Fuse carrier CH type
16A	16A	10 x 38
32A	32A	10 x 38

Poles	Frequency Hz	Voltage V	Earthing contact position h	Part No.	Colour	Part No.	Colour
2P+Ⓢ	50 and 60	100 - 130	4	TM 1643 IS Ⓢ	Yellow	TM 3243KIS Ⓢ	Yellow
	50 and 60	200 - 250	6	TM 1663 IS Ⓢ	Blue	TM 3263KIS Ⓢ	Blue
	50 and 60	380 - 415	9	TM 1693 IS Ⓢ	Red	TM 3293KIS Ⓢ	Red
	50 and 60	480 - 500	7	TM 1673 IS Ⓢ	Black	TM 3273KIS Ⓢ	Black
	50 and 60	ins. transformer	12	TM 16123 IS Ⓢ	A.V.	TM 32123KIS Ⓢ	A.V.
	> 300 - 500	> 50	2	TM 1623 IS Ⓢ	A.V.	TM 3223KIS Ⓢ (up to 400V)	A.V.
3P+Ⓢ	50 and 60	100 - 130	4	TM 1644 IS Ⓢ	Yellow	TM 3244KIS Ⓢ	Yellow
	50 and 60	200 - 250	9	TM 1694 IS Ⓢ	Red	TM 3294KIS Ⓢ	Red
	50 and 60	380 - 415	6	TM 1664 IS Ⓢ	Blue	TM 3264KIS Ⓢ	Blue
	60	440 - 460	11	TM 16114 IS Ⓢ	Black	TM 32114KIS Ⓢ	Black
	50 and 60	480 - 500	7	TM 1674 IS Ⓢ	Black	TM 3274KIS Ⓢ	Black
	50	380	3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black
	60	440	3	TM 1634 IS Ⓢ	Black	TM 3234KIS Ⓢ	Black
	100 - 300	> 50	10	TM 16104 IS Ⓢ	A.V.	TM 32104KIS Ⓢ (up to 400V)	A.V.
	> 300 - 500	> 50	2	TM 1624 IS Ⓢ	A.V.	TM 3224KIS Ⓢ (up to 400V)	A.V.
	3P+N+Ⓢ	50 and 60	57/100 - 75/130	4	TM 1645 IS Ⓢ	Yellow	TM 3245KIS Ⓢ
50 and 60		120/208 - 144/250	9	TM 1695 IS Ⓢ	Red	TM 3295KIS Ⓢ	Red
50 and 60		200/346 - 240/415	6	TM 1665 IS Ⓢ	Blue	TM 3265KIS Ⓢ	Blue
50 and 60		277/480 - 288/500	7	TM 1675 IS Ⓢ	Black	TM 3275KIS Ⓢ	Black
60		250/440 - 265/460	11	TM 16115 IS Ⓢ	Black	TM 32115KIS Ⓢ	Black
50		220/380	3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black
60		250/440	3	TM 1635 IS Ⓢ	Black	TM 3235KIS Ⓢ	Black
> 300 - 500		> 50	2	TM 1625 IS Ⓢ	A.V.	TM 3225KIS Ⓢ (up to 400V)	A.V.

Legend
A.V. = Colour according to voltage
*) Green may be used together with the colour of the operating range for frequencies above 60 Hz and up to a maximum of 500 Hz

Accessories for socket-outlet combinations

TM 1145 TB (page 24) with 1 plate TM 1114 DB (page 26) with 2 plates

TM 1114 GB (page 27)

Accessories for assembly on control panels

QP V - QG V

page 31

Dimensions indicated are not binding and may be changed without prior notice.

dimensions in mm

Poles	A	B
2P+Ⓢ	133	276
3P+Ⓢ	135	276
3P+N+Ⓢ	140	277

dimensions in mm

Poles	A
2P+Ⓢ	146
3P+Ⓢ	146
3P+N+Ⓢ	151

メモ

mmで示されている寸法は拘束力がなく、予告なく変更される場合があります。