


Part number

BE 1665



Interlocked switched socket-outlet, BE series, 3 poles + N + PE, 6 h (red), 16 A, 200/346 ÷ 240/415 V, without fuse-carrier

| Product description | | Material properties | |
|--|---|----------------------------------|--|
| Product type | Interlocked switched socket-outlet | Colour | RAL 7035 grey, RAL 3000 red |
| Series | BE | | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 3 poles + N +  | RoHs conformity | 50 |
| Clock position | 6 | China RoHs - EFUP | 50 |
| Size | Socket centre distance 114 x 228 mm | REACH SVHC substances | Yes Lead |
| Specification | Without fuse-carrier | SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Technical data | | Approvals / Standards | |
| Current | 16 A | Reference standard | EN 60309-1, -2 e -4 |
| Voltage | 200/346 ÷ 240/415 V | General ordering information | |
| IP degree of protection | IP67 | EAN13 code | 8015747003476 |
| Further technical details | | Packaging Information | |
| Weight | 1.190,00 g | Sub-packaging length | 116,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging height | 130,00 mm |
| IK rating (impact degree of protection) | IK10 | Sub-packaging width | 230,00 mm |
| | | Sub-packaging weight | 1,19 kg |
| | | Sub-packaging volume | 3,47 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747003490 |