


Part number

BK 1694



Interlocked switched socket-outlet, BK series, 3 poles + PE, 9 h (blue), 16 A, 200 ÷ 250 V, sectionable fuse carrier 10 x 38 mm

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | BK |
| N. of poles | 3 poles +  |
| Clock position | 9 |
| Size | Socket centre distance 114 x 228 mm |
| Specification | Sectionable fuse carrier 10 x 38 mm |

Technical data

| | |
|--------------------------------|-------------|
| Current | 16 A |
| Voltage | 200 ÷ 250 V |
| IP degree of protection | IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.306,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 5015 blue |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | F6799547-ab84-42f2-938f-233ba663766d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747004626 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|----------------------|
| Sub-packaging length | 116,00 mm |
| Sub-packaging height | 130,00 mm |
| Sub-packaging width | 230,00 mm |
| Sub-packaging weight | 1,31 kg |
| Sub-packaging volume | 3,47 dm ³ |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747004633 |

Part number

BK 1694



Catalogue drawings



| BK | | A | B |
|-----|------------|-----|----|
| 16A | 2P + ⊕ | 105 | 50 |
| | 3P + ⊕ | 105 | 50 |
| | 3P + N + ⊕ | 110 | 50 |
| 32A | 2P + ⊕ | 140 | 58 |
| | 3P + ⊕ | 140 | 58 |
| | 3P + N + ⊕ | 140 | 58 |