


Part number

# BK 3225



Interlocked switched socket-outlet, BK series, 3 poles + N + PE, 2 h (green), 32 A, > 50 V, sectionable fuse carrier 10 x 38 mm

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | BK  |
| <b>N. of poles</b>    | 3 poles + N +  |
| <b>Clock position</b> | 2   |
| <b>Specification</b>  | Sectionable fuse carrier 10 x 38 mm   |

#### Technical data

|                                |        |
|--------------------------------|--------|
| <b>Current</b>                 | 32 A   |
| <b>Voltage</b>                 | > 50 V |
| <b>IP degree of protection</b> | IP67   |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|               |               |
|---------------|---------------|
| <b>Colour</b> | RAL 7035 grey |
|---------------|---------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747147187 |
|-------------------|---------------|

Part number

# BK 3225



Catalogue drawings



| BK  |            | A   | B  |
|-----|------------|-----|----|
| 16A | 2P + ⊕     | 105 | 50 |
|     | 3P + ⊕     | 105 | 50 |
|     | 3P + N + ⊕ | 110 | 50 |
| 32A | 2P + ⊕     | 140 | 58 |
|     | 3P + ⊕     | 140 | 58 |
|     | 3P + N + ⊕ | 140 | 58 |