

Part number

# CDFD 0.3



Female crimp contact, CD series, 10 A, turned gold plated, wire cross section 0,14 - 0,37 mm<sup>2</sup>, AWG 26 - 22

#### Product description

<b>Product type</b>	Crimp contact
<b>Series</b>	CD
<b>Gender</b>	Female

#### Technical data

<b>Current</b>	10 A
<b>Wire cross-section</b>	0,14 mm <sup>2</sup> - 0,37 mm <sup>2</sup>
<b>AWG size</b>	26 - 22
<b>Contact type</b>	Turned gold plated

#### Further technical details

<b>Weight</b>	0,70 g
<b>Operating temperature range (min, max)</b>	-40°C ... +125°C
<b>Conductors stripping length</b>	8 mm

#### Material properties

<b>Main material</b>	Copper alloy
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight

#### China RoHs - EFUP

50

#### REACH SVHC substances

Yes  
Lead

**SCIP number** C0979fba-9907-458f-a94a-db781440f273

#### Approvals / Standards

<b>Certifications</b>	CSA, EAC
<b>UL</b>	ECBT2

#### General ordering information

<b>EAN13 code</b>	8015747014809
<b>eCl@ss 8.1</b>	27440204
<b>ETIM 7.0</b>	EC000796

#### Packaging Information

<b>Packaging length</b>	112,00 mm
<b>Packaging height</b>	95,00 mm
<b>Packaging width</b>	117,00 mm
<b>Packaging weight</b>	1,26 kg
<b>Packaging volume</b>	1,24 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	1600 Pcs
<b>Packaging EAN code</b>	8015747206808
<b>Sub-packaging length</b>	50,00 mm
<b>Sub-packaging height</b>	44,00 mm
<b>Sub-packaging width</b>	50,00 mm
<b>Sub-packaging weight</b>	0,16 kg
<b>Sub-packaging volume</b>	0,11 dm <sup>3</sup>
<b>Sub-packaging description</b>	Plastic box
<b>Sub-packaging quantity</b>	200 Pcs
<b>Sub-packaging EAN barcode</b>	8015747014816

Part number

# CDFD 0.3



## Catalogue drawings



### CDF and CDM contacts

conductor section mm <sup>2</sup>	conductor slot $\varnothing A$ (mm)	conductors stripping length B (mm)
0,14-0,37	0,9	8
0,5	1,1	8
0,75	1,3	8
1,0	1,45	8
1,5	1,8	8
2,5	2,2	6