

Part number

CDMA 0.3



Male crimp contact, CD series, 10 A, turned silver plated, wire cross section 0,14 - 0,37 mm², AWG 26 - 22

Product description

Product type	Crimp contact
Series	CD
Gender	Male

Technical data

Current	10 A
Wire cross-section	0,14 mm ² - 0,37 mm ²
AWG size	26 - 22
Contact type	Turned silver plated

Further technical details

Contact resistance	≤ 0,3 mΩ
Weight	0,70 g
Operating temperature range (min, max)	-40°C ... +125°C
Conductors stripping length	8 mm

Material properties

Main material	Copper alloy
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	C0979fba-9907-458f-a94a-db781440f273

Approvals / Standards

Certifications	CSA, EAC
UL	ECBT2

General ordering information

EAN13 code	8015747015202
eCl@ss 8.1	27440204
ETIM 7.0	EC000796

Packaging Information

Packaging length	112,00 mm
Packaging height	95,00 mm
Packaging width	117,00 mm
Packaging weight	1,27 kg
Packaging volume	1,24 dm ³
Packaging description	Carton box
Packaging quantity	1600 Pcs
Packaging EAN code	8015747104012
Sub-packaging length	50,00 mm
Sub-packaging height	44,00 mm
Sub-packaging width	50,00 mm
Sub-packaging weight	0,16 kg
Sub-packaging volume	0,11 dm ³
Sub-packaging description	Plastic box
Sub-packaging quantity	200 Pcs
Sub-packaging EAN barcode	8015747015219

Part number

CDMA 0.3



Catalogue drawings



CDF and CDM contacts

conductor section mm ²	conductor slot $\varnothing A$ (mm)	conductors stripping length B (mm)
0,14-0,37	0,9	8
0,5	1,1	8
0,75	1,3	8
1,0	1,45	8
1,5	1,8	8
2,5	2,2	6