



Part number

CDYM 07



Male insert, CDY series, AXYR® spring push-in terminal connection without tools, 7 poles + PE, 10 A 250 V 4 kV 3, size "21.21"

| Product description | |
|---|--|
| Product type | Insert |
| Series | CDY |
| Connection type | AXYR® high density spring terminal connection without tools |
| Gender | Male |
| N. of poles | 7 poles +  |
| Size | Size "21.21" |
| Technical data | |
| Current | 10 A |
| Voltage | 250 V |
| Rated impulse withstand voltage | 4 kV |
| Pollution degree | 3 |
| Contact type | Turned silver plated |
| IP degree of protection | IP20 without enclosure, IP44/IP66/IP67/IP68/IP69 with enclosure |
| Further technical details | |
| Characteristics according to EN 61984 | 10A 250V 4kV 3; 10A 230/400V 4kV 2 |
| Mating cycles | ≥ 500 |
| Insulation resistance | ≥ 10 GΩ |
| Contact resistance | ≤ 3 mΩ |
| Weight | 16,50 g |
| Operating temperature range (min, max) | -40 °C ... +125 °C |
| Conductors stripping length | 9...11 mm |
| UL 94 flammability rating | V-0 |


| Material properties | |
|----------------------------------|--|
| Main material | Polycarbonate (PC) |
| Other materials | Contacts: copper alloy |
| Colour | RAL 7032 grey |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| General ordering information | |
| EAN13 code | 8015747292863 |
| eCl@ss 8.1 | 27440205 |
| ETIM 7.0 | EC000438 |
| Packaging Information | |
| Packaging length | 280,00 mm |
| Packaging height | 170,00 mm |
| Packaging width | 185,00 mm |
| Packaging weight | 2,03 kg |
| Packaging volume | 8,81 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 100 Pcs |
| Packaging EAN code | 8015747292870 |
| Sub-packaging weight | 0,02 kg |
| Sub-packaging description | Plastic bag |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747292887 |

Part number

CDYM 07



Catalogue drawings



Derating curves

CDY 07 poles connector inserts Maximum current load derating diagram

