

Part number

CHIN 10



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "57.27"

Product description

Product type	Bulkhead mounting housing
Series	LS-TYPE
Closing type	With 2 levers
Size	Size 57.27
Cable entry	Without cable entry

Technical data

IP degree of protection	IP65
--------------------------------	------

Further technical details

Weight	86,00 g
Operating temperature range (min, max)	-40°C...+125°C

Material properties

Other materials	Lever: Polyamide (PA) Gasket: NBR
Colour	RAL 9005 black
RoHs conformity	Compliant
China RoHs - EFUP	E
REACH SVHC substances	No

Approvals / Standards

Certifications	DNV, BV
UL	ECBT2
cUL	ECBT8

General ordering information

EAN13 code	8015747163088
eCl@ss 8.1	27440202
ETIM 7.0	EC000437

Packaging Information

Packaging length	305,00 mm
Packaging height	180,00 mm
Packaging width	275,00 mm
Packaging weight	3,44 kg
Packaging volume	15,10 dm ³
Packaging description	Carton box
Packaging quantity	40 Pcs
Packaging EAN code	8015747187589
Sub-packaging weight	0,43 kg
Sub-packaging description	Plastic packaging
Sub-packaging quantity	5 Pcs
Sub-packaging EAN barcode	8015747187596

Part number CHIN 10



Catalogue drawings

Catalogue drawings

CH.N - MA, MF.N custodie grandezza "57.27" versione LS-TYPE

frutti inseribili: pag.

CDD	42 poli + @	61 *
CDE	18 poli + @	81 *
CSH	10 poli + @	89 *
CCE	10 poli + @	90 *
CNE,CSE,JCNE,JCSE	10 poli + @	97 e 107 *
CSS	10 poli + @	119 *
CTE, CTSE **	10 poli + @	127 *
CMSE	3+2 (aux) poli + @	135 *
CMCE	3+2 (aux) poli + @	134 *
CX	8/24 poli + @	151 *
MIXO	3 moduli	160+195 *

interassi fissaggio frutti: 57 x 27 mm

* riferimenti di pagina catalogo CN.12

descrizione	codice articolo	uscita M	codice articolo	uscita M
custodia da incasso, con 2 leve	CHIN 10			
custodia da parete, alta, con 2 leve	MAPN 10.32	32		
con pinoli, uscita orizzontale			MHON 10.25	25
con pinoli, uscita orizzontale, alta			MFON 10.32	32
con pinoli, uscita verticale			MHVN 10.25	25
con pinoli, uscita verticale, alta			MFVN 10.32	32

** solo nella custodia CHIN 10

dim. di fissaggio custodia da incasso in mm

- verniciatura a forno con polvere epossipolistere nera RAL 9005
- leva di chiusura in materiale termoplastico auto-attingente, di colore nero RAL 9005 (leva di ricambio pag. 12)

le misure indicate non sono impegnative e possono essere variate senza alcun preavviso

6

CH.N - MA, MF.N enclosures size "57.27" LS-TYPE version

inserts: page

CDD	42 poles + @	61 *
CDE	18 poles + @	81 *
CSH	10 poles + @	89 *
CCE	10 poles + @	90 *
CNE,CSE,JCNE,JCSE	10 poles + @	97 and 107 *
CSS	10 poles + @	119 *
CTE, CTSE **	10 poles + @	127 *
CMSE	3+2 (aux) poles + @	135 *
CMCE	3+2 (aux) poles + @	134 *
CX	8/24 poles + @	151 *
MIXO	3 modules	160+195 *

insert centre distance: 57 x 27 mm

* refer to catalogue page CN.12

description	part no.	entry M	part no.	entry M
bulkhead mounting housing, with 2 levers	CHIN 10			
surface mounting housing, high construction, with 2 levers	MAPN 10.32	32		
with pegs, side entry			MHON 10.25	25
with pegs, side entry, high construction			MFON 10.32	32
with pegs, top entry			MHVN 10.25	25
with pegs, top entry, high construction			MFVN 10.32	32

** only in the CHIN 10 enclosure

panel cut-out for bulkhead mounting housing in mm

- kin powder coating with RAL 9005 black epoxy polyester powder
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

6