

Part number

# CX 02 CHM



Male modular insert, Mixo series, crimp connection, 2 poles, 1 module, 16 A 2500 V 15 kV 3, with heat-shrinking tube

#### Product description

<b>Product type</b>	Modular insert
<b>Series</b>	Mixo
<b>Connection type</b>	Crimp connection
<b>Gender</b>	Male
<b>N. of poles</b>	2 poles
<b>Size</b>	1 module
<b>Specification</b>	With heat-shrinking tube

#### Technical data

<b>Current</b>	16 A
<b>Voltage</b>	2500 V
<b>Rated impulse withstand voltage</b>	15 kV
<b>Pollution degree</b>	3
<b>IP degree of protection</b>	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure

#### Further technical details

<b>Characteristics according to EN 61984</b>	16A 2500V 15kV 3
<b>Mating cycles</b>	≥ 500
<b>Insulation resistance</b>	≥ 10 GΩ
<b>Contact resistance</b>	≤ 1 mΩ
<b>Weight</b>	28,00 g
<b>Operating temperature range (min, max)</b>	-40 °C ... +125 °C
<b>UL 94 flammability rating</b>	V-0

#### Material properties

<b>Main material</b>	Polycarbonate
<b>Colour</b>	RAL 7032 grey
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV
-----------------------	-----

#### General ordering information

<b>EAN13 code</b>	8015747203081
<b>eCl@ss 8.1</b>	27440205
<b>ETIM 7.0</b>	EC000438

#### Packaging Information


<b>Sub-packaging weight</b>	0,03 kg
<b>Sub-packaging description</b>	Plastic bag
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747203098

Part number

# CX 02 CHM




## Catalogue drawings



## Derating curves

**CX 02 CH, 2 poles connector inserts**  
**Maximum current load derating diagram**


M



F

contacts side (front view)

side with reference arrow ▲



- 1 frame slot