

Part number

# CX 04 BM



Male modular insert, Mixo Bus series, coaxial, 4 poles, 10 A 50 V 0,8 kV 3, shielded

Product description		Material properties	
<b>Product type</b>	Modular insert	<b>Main material</b>	Polycarbonate
<b>Series</b>	Mixo Bus	<b>Colour</b>	RAL 7032 grey
<b>Connection type</b>	Coaxial	<b>RoHs conformity</b>	Compliant
<b>Gender</b>	Male	<b>China RoHs - EFUP</b>	E
<b>N. of poles</b>	4 poles	<b>REACH SVHC substances</b>	No
<b>Specification</b>	Shielded	Approvals / Standards	
Technical data		<b>Reference standard</b>	EN 61984:2009-06
<b>Current</b>	10 A	<b>Certifications</b>	CSA, CQC, DNV, EAC
<b>Voltage</b>	50 V	<b>UL</b>	ECBT2
<b>Rated impulse withstand voltage</b>	0,8 kV	<b>cUL</b>	ECBT8
<b>Pollution degree</b>	3	General ordering information	
<b>Rated voltage according to UL/CSA</b>	50 V	<b>EAN13 code</b>	8015747096010
<b>IP degree of protection</b>	IP20 without enclosure, IP65/IP66/IP68/IP69 with enclosure	<b>eCl@ss 8.1</b>	27440205
Further technical details		<b>ETIM 7.0</b>	EC000438
<b>Characteristics according to EN 61984</b>	10A 50V 0.8kV 3	Packaging Information	
<b>Insulation resistance</b>	≥ 10 GΩ	<b>Packaging weight</b>	0,67 kg
<b>Contact resistance</b>	≤ 3 mΩ	<b>Packaging description</b>	Carton box
<b>Weight</b>	7,70 g	<b>Packaging quantity</b>	10 Pcs
<b>Operating temperature range (min, max)</b>	-40°C ... +85°C	<b>Packaging EAN code</b>	8015747096027
<b>UL 94 flammability rating</b>	V-0	<b>Sub-packaging length</b>	185,00 mm
		<b>Sub-packaging height</b>	40,00 mm
		<b>Sub-packaging width</b>	155,00 mm
		<b>Sub-packaging weight</b>	0,07 kg
		<b>Sub-packaging volume</b>	1,15 dm <sup>3</sup>
		<b>Sub-packaging description</b>	Plastic bag
		<b>Sub-packaging quantity</b>	1 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747096034

Part number

# CX 04 BM



Catalogue drawings

**CX 04 BF**

**CX 04 BM**

