

Part number

# CXF 4/8 RY



Female insert, CX RY series, screw terminal connection, 4 + 8 poles + PE, 80 A 400 V 6 kV 3 / 16 A 230/400 V 4 kV 3, size "104.27", for applications up to 180°C

Product description		Material properties	
<b>Product type</b>	Insert	<b>Main material</b>	Polyphenylene sulfide (PPS)
<b>Series</b>	CX RY	<b>Other materials</b>	Contacts: copper alloy
<b>Connection type</b>	Screw terminal connection		Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>Gender</b>	Female	<b>RoHs conformity</b>	
<b>N. of poles</b>	4 poles +	<b>China RoHs - EFUP</b>	50
<b>Auxiliary poles</b>	8 poles	<b>REACH SVHC substances</b>	Yes
<b>Size</b>	Size 104.27		Lead
<b>Specification</b>	For applications up to 180°C	<b>SCIP number</b>	1a9c93ff-0445-4a16-81e3-1609ac5274d6
Technical data		Approvals / Standards	
<b>Current</b>	80 A	<b>Reference standard</b>	EN 61984:2009-06
<b>Voltage</b>	400 V	<b>Certifications</b>	CSA, CQC, DNV, BV, EAC
<b>Rated impulse withstand voltage</b>	6 kV	<b>UL</b>	ECBT2
<b>Pollution degree</b>	3	<b>cUL</b>	ECBT8
<b>Rated voltage according to UL/CSA</b>	600 V	General ordering information	
<b>Wire cross-section</b>	4,00 mm <sup>2</sup> - 16,00 mm <sup>2</sup>	<b>EAN13 code</b>	8015747042390
<b>AWG size</b>	12 - 6	<b>eCl@ss 8.1</b>	27440205
<b>Contact type</b>	Turned silver plated	<b>ETIM 7.0</b>	EC000438
<b>IP degree of protection</b>	IP20 without enclosure, IP65 with enclosure	Packaging Information	
Further technical details		<b>Sub-packaging length</b>	113,00 mm
<b>Mating cycles</b>	≥ 500	<b>Sub-packaging height</b>	36,00 mm
<b>Insulation resistance</b>	≥ 10 GΩ	<b>Sub-packaging width</b>	180,00 mm
<b>Weight</b>	160,00 g	<b>Sub-packaging weight</b>	0,80 kg
<b>Operating temperature range (min, max)</b>	-40°C ... +180°C	<b>Sub-packaging volume</b>	0,73 dm <sup>3</sup>
<b>UL 94 flammability rating</b>	V-0	<b>Sub-packaging description</b>	Carton tray
		<b>Sub-packaging quantity</b>	5 Pcs
		<b>Sub-packaging EAN barcode</b>	8015747042406