


Part number

# KI 16114 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V, with compartment for modular units, 7 DIN-rail modules EN 60715

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | KI..RI5   |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 11  |
| <b>Cable entry</b>    | Pg29  |
| <b>Specification</b>  | With compartment for modular units, 7 DIN-rail modules EN 60715                             |

#### Technical data

|                                |             |
|--------------------------------|-------------|
| <b>Current</b>                 | 16 A        |
| <b>Voltage</b>                 | 440 ÷ 460 V |
| <b>IP degree of protection</b> | IP55        |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|               |                             |
|---------------|-----------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747150712 |
|-------------------|---------------|

Part number

# KI 16114 RI5



## Catalogue drawings

