


Part number

KI 1664 RI5



Interlocked switched socket-outlet, KI series, 3 poles + PE, 6 h (red), 16 A, 380 ÷ 415 V, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | KI..RI5 |
| N. of poles | 3 poles +  |
| Clock position | 6 |
| Size | 143x343 fixing plates FC xx53 TB |
| Cable entry | Pg29 |
| Specification | With compartment for modular units, 7 DIN-rail modules EN 60715 |

Technical data

| | |
|--------------------------------|-------------|
| Current | 16 A |
| Voltage | 380 ÷ 415 V |
| IP degree of protection | IP55 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.718,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747048545 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|-----------------------|
| Packaging length | 400,00 mm |
| Packaging height | 165,00 mm |
| Packaging width | 170,00 mm |
| Packaging weight | 1,72 kg |
| Packaging volume | 11,22 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 1 Pcs |
| Packaging EAN code | 8015747048552 |

Part number

KI 1664 RI5



Catalogue drawings

