


Part number

# KI 1693 IB6



Interlocked switched socket-outlet, IB6 series,  
2 poles + PE, 9 h (red), 16 A, 380 ÷ 415 V,  
sectionable fuse carrier 10 x 38 mm

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | KI...IB6  |
| <b>N. of poles</b>    | 2 poles +  |
| <b>Clock position</b> | 9   |
| <b>Size</b>           | 114x228 fixing plates FC xx41 TB  |
| <b>Cable entry</b>    | M25   |
| <b>Specification</b>  | Sectionable fuse carrier 10 x 38 mm   |

#### Technical data

|                                |             |
|--------------------------------|-------------|
| <b>Current</b>                 | 16 A        |
| <b>Voltage</b>                 | 380 ÷ 415 V |
| <b>IP degree of protection</b> | IP66        |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Weight</b>                                  | 938,00 g        |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK10            |

#### Material properties

|                              |  |
|------------------------------|--|
| <b>Colour</b>                | RAL 7035 grey, RAL 3000 red  |
| <b>RoHs conformity</b>       | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>China RoHs - EFUP</b>     | 50   |
| <b>REACH SVHC substances</b> | Yes<br>Lead  |
| <b>SCIP number</b>           | F6799547-ab84-42f2-938f-233ba663766d   |

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747199469 |
|-------------------|---------------|

#### Packaging Information

|                                  |                       |
|----------------------------------|-----------------------|
| <b>Packaging length</b>          | 520,00 mm             |
| <b>Packaging height</b>          | 305,00 mm             |
| <b>Packaging width</b>           | 490,00 mm             |
| <b>Packaging weight</b>          | 14,85 kg              |
| <b>Packaging volume</b>          | 77,71 dm <sup>3</sup> |
| <b>Packaging description</b>     | Carton box            |
| <b>Packaging quantity</b>        | 15 Pcs                |
| <b>Packaging EAN code</b>        | 8015747210300         |
| <b>Sub-packaging length</b>      | 270,00 mm             |
| <b>Sub-packaging height</b>      | 125,00 mm             |
| <b>Sub-packaging width</b>       | 120,00 mm             |
| <b>Sub-packaging weight</b>      | 0,99 kg               |
| <b>Sub-packaging volume</b>      | 4,05 dm <sup>3</sup>  |
| <b>Sub-packaging description</b> | Carton box            |
| <b>Sub-packaging quantity</b>    | 1 Pcs                 |
| <b>Sub-packaging EAN barcode</b> | 8015747210317         |