


Part number

KI 63123 RI5



Interlocked switched socket-outlet, KI series, 2 poles + PE, 12 h (white), 63 A, with compartment for modular units, 7 DIN-rail modules EN 60715

Product description

| | |
|-----------------------|---------------------------------------------------------------------------------------------|
| Product type | Interlocked switched socket-outlet |
| Series | KI..RI5 |
| N. of poles | 2 poles +  |
| Clock position | 12 |
| Cable entry | Pg29 |
| Specification | With compartment for modular units, 7 DIN-rail modules EN 60715 |

Technical data

| | |
|--------------------------------|------------------|
| Current | 63 A |
| Voltage | ins. transformer |
| IP degree of protection | IP55 |

Further technical details

| | |
|------------------------------------------------|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-------------------------------|
| Colour | RAL 7035 grey, RAL 9010 white |
|---------------|-------------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747151474 |
|-------------------|---------------|

Part number

KI 63123 RI5



Catalogue drawings

