

Part number

# MHON 06 L25



Hood, LS-TYPE series, with 2 pegs, M25 side cable entry, size "44.27"

#### Product description

<b>Product type</b>	Hood
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 2 pegs
<b>Size</b>	Size 44.27
<b>Cable entry</b>	Side cable entry M25

#### Technical data

<b>IP degree of protection</b>	IP65
--------------------------------	------

#### Further technical details

<b>Weight</b>	95,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747194181
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437


#### Packaging Information

<b>Sub-packaging weight</b>	0,48 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747194198

# Part number MHON 06 L25



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures**      size "44.27"      LS-TYPE version

<p>inserts: <span style="float: right;">page</span></p> <p>CDD ..... 24 poles + ⊕ 59 *</p> <p>CQE ..... 10 poles + ⊕ 80 *</p> <p>CSH ..... 6 poles + ⊕ 88 *</p> <p>CCE ..... 6 poles + ⊕ 94 *</p> <p>CNE, CSE, JONE, JOSE 6 poles + ⊕ 95 and 103 *</p> <p>CSS ..... 6 poles + ⊕ 118 *</p> <p>CTE, CTSE **) ..... 6 poles + ⊕ 126 *</p> <p>MIXO ..... 2 modules 160+195 *</p> <p>insert centre distance: 44 x 27 mm</p> <p>* refer to catalogue page CN.12</p>	<p><b> housings with single lever</b></p>	<p><b> hoods with 2 pegs</b></p>
description	part no.    entry	part no.    entry
bulkhead mounting housing, with lever	<b>CHIN 06 L</b>	
surface mounting housing, high construction, with lever	<b>MAPN 06 L32    32</b>	
with pegs, side entry		<b>MHON 06 L25    25</b>
with pegs, side entry, high construction		<b>MFON 06 L25    25</b>
with pegs, top entry		<b>MHVN 06 L25    25</b>
with pegs, top entry, high construction		<b>MFVN 06 L25    25</b>
<p>**) only in the CHIN 06 L enclosure</p> <p>panel cut-out for bulkhead mounting housing in mm</p> <p>- kiln powder coating with RAL 9005 black epoxy polyester powder - RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)</p>	<p>dimensions in mm</p> <p><b>CHIN 06 L</b></p> <p><b>MAPN 06 L32</b></p>	<p>dimensions in mm</p> <p><b>MFON 06 L25</b></p> <p><b>MFVN 06 L25</b></p> <p><b>MHON 06 L25</b></p> <p><b>MHVN 06 L25</b></p>
<p>dimensions shown are not binding and may be changed without notice</p>		