


Part number

PE 16114 SI



Flush-mounting plug, PLUSO series, 3 poles + PE, 11 h (red), 16 A, 440 ÷ 460 V

Product description

| | |
|-----------------------|---|
| Product type | Plug Flush-mounting |
| Series | PE...SI, PLUSO |
| N. of poles | 3 poles +  |
| Clock position | 11 |

Technical data

| | |
|--------------------------------|-------------|
| Current | 16 A |
| Voltage | 440 ÷ 460 V |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Operating temperature range (min, max) | -25°C ... +40°C |
|---|-----------------|

Material properties

| | |
|---------------|-----------------------------|
| Colour | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747154499 |
|-------------------|---------------|

Part number

PE 16114 SI



Catalogue drawings

(16 / 32A) PE ... SI



| PE ... SI | A | B | C | D | E | F | G | X | Y |
|-----------------|----|-----|-----|-----|----|----|------|----|----|
| 16A 2P+⊕ | 65 | 82 | 126 | 81 | 41 | 43 | 21,5 | 52 | 60 |
| | 65 | 82 | 126 | 81 | 47 | 43 | 21,5 | 52 | 60 |
| | 90 | 100 | 146 | 93 | 54 | 60 | 27,5 | 77 | 85 |
| 32A 2P+⊕ | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 77 | 85 |
| | 90 | 100 | 160 | 101 | 55 | 60 | 27,5 | 77 | 85 |
| | 90 | 100 | 160 | 106 | 62 | 60 | 27,5 | 77 | 85 |