

Part number

PE 1624 PP



Wall-mounting socket outlet, PLUSO series, 3 poles + PE, 2 h (green), 16 A, > 50 V

Product description

| | |
|-----------------------|---|
| Product type | Socket Wall-mounting |
| Series | PE...PP, PLUSO |
| N. of poles | 3 poles +  |
| Clock position | 2 |

Technical data

| | |
|--------------------------------|--------|
| Current | 16 A |
| Voltage | > 50 V |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Weight | 220,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|---------------|-------------------------------|
| Colour | RAL 7035 grey, RAL 6017 green |
|---------------|-------------------------------|

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747063319 |
|-------------------|---------------|

Part number

PE 1624 PP



Catalogue drawings

(16 / 32A) PE ... PP



| PE ... PP | A | B | C | D | E | G | H | X | Y | Pg Ø | Z Ø | |
|------------|--------|----|-----|-----|-----|----|-----|----|----|------|-----|-----|
| 16A | 2P+⊕ | 70 | 82 | 126 | 92 | 20 | Ø22 | 16 | 53 | 65 | 16 | 4,5 |
| | 3P+⊕ | 70 | 82 | 126 | 92 | 20 | Ø22 | 16 | 53 | 65 | 16 | 4,5 |
| | 3P+N+⊕ | 70 | 82 | 132 | 106 | 20 | Ø22 | 16 | 53 | 65 | 16 | 4,5 |
| 32A | 2P+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21 | 6,5 |
| | 3P+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21 | 6,5 |
| | 3P+N+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21 | 6,5 |