

Part number

PE 1693 SA



Mobile plug, PLUSO series, 2 poles + PE, 9 h (red), 16 A, 380 ÷ 415 V, angled

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7035 grey, RAL 3000 red
Series	PE...SA, PLUSO	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	2 poles +	China RoHs - EFUP	50
Clock position	9	REACH SVHC substances	Yes Lead
Specification	Angled	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Technical data		Approvals / Standards	
Current	16 A	Reference standard	EN 60309-1 and -2
Voltage	380 ÷ 415 V	General ordering information	
IP degree of protection	IP44	EAN13 code	8015747065412
Further technical details		Packaging Information	
Weight	98,00 g	Sub-packaging length	140,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging height	135,00 mm
		Sub-packaging width	235,00 mm
		Sub-packaging weight	0,98 kg
		Sub-packaging volume	4,44 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	10 Pcs
		Sub-packaging EAN barcode	8015747065429

Part number

PE 1693 SA



Catalogue drawings

(16 / 32A) PE ... SA



PE...SA	A	B	C	Pg Ø
16A 2P+⊕	100	77	59	13,5
3P+⊕	100	84	68	16
3P+N+⊕	106	91	77	16
32A 2P+⊕	131	100	82	21
3P+⊕	131	100	82	21
3P+N+⊕	131	107	93	21