


Part number

PE 32114 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 11 h (red), 32 A, 440 ÷ 460 V

Product description

| | |
|-----------------------|---|
| Product type | Socket Mobile |
| Series | PE...PV, PLUSO |
| N. of poles | 3 poles +  |
| Clock position | 11 |

Technical data

| | |
|--------------------------------|-------------|
| Current | 32 A |
| Voltage | 440 ÷ 460 V |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Weight | 245,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 3000 red |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747066006 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|-----------------------|
| Packaging length | 330,00 mm |
| Packaging height | 175,00 mm |
| Packaging width | 295,00 mm |
| Packaging weight | 3,00 kg |
| Packaging volume | 17,04 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747112000 |


Part number

PE 32114 PV



Catalogue drawings

(16 / 32A) PE ... PV



| PE...PV | A | B | Ø min | Ø max |
|-----------------|-------|----|-------|-------|
| 16A 2P+⊕ | 157,5 | 68 | 7 | 17 |
| 3P+⊕ | 164,5 | 76 | 7 | 17 |
| 3P+N+⊕ | 183,5 | 83 | 9 | 22 |
| 32A 2P+⊕ | 200,5 | 87 | 9 | 22 |
| 3P+⊕ | 200,5 | 87 | 9 | 22 |
| 3P+N+⊕ | 200,5 | 91 | 9 | 22 |