


Part number

# PE 3255 SA



Mobile plug, PLUSO series, 3 poles + N + PE, 5 h (black), 32 A, 347/600 ÷ 400/690 V, angled

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Plug<br>Mobile  |
| <b>Series</b>         | PE...SA, PLUSO  |
| <b>N. of poles</b>    | 3 poles + N +  |
| <b>Clock position</b> | 5   |
| <b>Specification</b>  | Angled  |

#### Technical data

|                                |                     |
|--------------------------------|---------------------|
| <b>Current</b>                 | 32 A                |
| <b>Voltage</b>                 | 347/600 ÷ 400/690 V |
| <b>IP degree of protection</b> | IP44                |

#### Further technical details

|   |                 |
|---|-----------------|
| <b>Operating temperature range (min, max)</b> | -25°C ... +40°C |
|---|-----------------|

#### Material properties

|               |                               |
|---------------|-------------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 9005 black |
|---------------|-------------------------------|

#### Approvals / Standards

|                           |                   |
|---------------------------|-------------------|
| <b>Reference standard</b> | EN 60309-1 and -2 |
|---------------------------|-------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747155670 |
|-------------------|---------------|

Part number

# PE 3255 SA



Catalogue drawings

(16 / 32A) PE ... SA



| PE...SA         | A   | B   | C  | Pg Ø |
|-----------------|-----|-----|----|------|
| <b>16A</b> 2P+⊕ | 100 | 77  | 59 | 13,5 |
| 3P+⊕            | 100 | 84  | 68 | 16   |
| 3P+N+⊕          | 106 | 91  | 77 | 16   |
| <b>32A</b> 2P+⊕ | 131 | 100 | 82 | 21   |
| 3P+⊕            | 131 | 100 | 82 | 21   |
| 3P+N+⊕          | 131 | 107 | 93 | 21   |