


Part number

PE 3275 PP



Wall-mounting socket outlet, PLUSO series, 3 poles + N + PE, 7 h (black), 32 A, 277/480 ÷ 288/500 V

Product description

| | |
|-----------------------|---|
| Product type | Socket Wall-mounting |
| Series | PE...PP, PLUSO |
| N. of poles | 3 poles + N +  |
| Clock position | 7 |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 32 A |
| Voltage | 277/480 ÷ 288/500 V |
| IP degree of protection | IP44 |

Further technical details

| | |
|---|-----------------|
| Weight | 337,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |

Material properties

| | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9005 black |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ca7de37f-add8-4b77-9861-279c94903ade |

Approvals / Standards

| | |
|---------------------------|-------------------|
| Reference standard | EN 60309-1 and -2 |
|---------------------------|-------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747067812 |
|-------------------|---------------|

Packaging Information

| | |
|------------------------------|-----------------------|
| Packaging length | 330,00 mm |
| Packaging height | 175,00 mm |
| Packaging width | 295,00 mm |
| Packaging weight | 3,55 kg |
| Packaging volume | 17,04 dm ³ |
| Packaging description | Carton box |
| Packaging quantity | 10 Pcs |
| Packaging EAN code | 8015747067829 |

Part number

PE 3275 PP



Catalogue drawings

(16 / 32A) PE ... PP



| PE ... PP | A | B | C | D | E | G | H | X | Y | Pg Ø | Z Ø | |
|------------|--------|----|-----|-----|-----|----|-----|----|----|------|-----|-----|
| 16A | 2P+⊕ | 70 | 82 | 126 | 92 | 20 | Ø22 | 16 | 53 | 65 | 16 | 4,5 |
| | 3P+⊕ | 70 | 82 | 126 | 92 | 20 | Ø22 | 16 | 53 | 65 | 16 | 4,5 |
| | 3P+N+⊕ | 70 | 82 | 132 | 106 | 20 | Ø22 | 16 | 53 | 65 | 16 | 4,5 |
| 32A | 2P+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21 | 6,5 |
| | 3P+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21 | 6,5 |
| | 3P+N+⊕ | 86 | 104 | 159 | 110 | 24 | Ø28 | 17 | 61 | 79 | 21 | 6,5 |