


Part number

PEW 3264 PV



Mobile socket outlet, PLUSO series, 3 poles + PE, 6 h (red), 32 A, 380 ÷ 415 V

Product description

Product type	Socket Mobile
Series	PEW...PV, PLUSO
N. of poles	3 poles + 
Clock position	6

Technical data

Current	32 A
Voltage	380 ÷ 415 V
IP degree of protection	IP67

Further technical details

Weight	285,00 g
Operating temperature range (min, max)	-25°C ... +40°C

Material properties

Colour	RAL 7035 grey, RAL 3000 red
RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
China RoHs - EFUP	50
REACH SVHC substances	Yes Lead
SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747075442
-------------------	---------------

Packaging Information

Packaging length	330,00 mm
Packaging height	175,00 mm
Packaging width	295,00 mm
Packaging weight	3,17 kg
Packaging volume	17,04 dm ³
Packaging description	Carton box
Packaging quantity	10 Pcs
Packaging EAN code	8015747075459


Part number

PEW 3264 PV



Catalogue drawings

(16 / 32A) PEW ... PV



PEW...PV	A	B	Ø min	Ø max
16A 2P+⊖	145	77	7	16
3P+⊖	145	85	7	16
3P+N+⊖	145	93	8	24
32A 2P+⊖	162	97	8	24
3P+⊖	162	97	8	24
3P+N+⊖	162	105	8	24