


Part number

# PEW 6393 PV



Mobile socket outlet, PLUSO series, 2 poles + PE, 9 h (red), 63 A, 380 ÷ 415 V

#### Product description

<b>Product type</b>	Socket Mobile
<b>Series</b>	PEW...PV, PLUSO
<b>N. of poles</b>	2 poles + 
<b>Clock position</b>	9

#### Technical data

<b>Current</b>	63 A
<b>Voltage</b>	380 ÷ 415 V
<b>IP degree of protection</b>	IP67

#### Further technical details

<b>Weight</b>	787,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C

#### Material properties

<b>Colour</b>	RAL 7035 grey, RAL 3000 red
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ca7de37f-add8-4b77-9861-279c94903ade

#### Approvals / Standards

<b>Reference standard</b>	EN 60309-1 and -2
---------------------------	-------------------

#### General ordering information

<b>EAN13 code</b>	8015747078108
-------------------	---------------

#### Packaging Information

<b>Packaging length</b>	300,00 mm
<b>Packaging height</b>	130,00 mm
<b>Packaging width</b>	200,00 mm
<b>Packaging weight</b>	1,79 kg
<b>Packaging volume</b>	7,80 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	2 Pcs
<b>Packaging EAN code</b>	8015747078115


Part number

# PEW 6393 PV



Catalogue drawings

(63 / 125A) PEW ... PV



PEW ... PV		A	B	Pg Ø
<b>63A</b>	2P+⊕	277	108,5	36
	3P+⊕	277	108,5	36
	3P+N+⊕	277	108,5	36
<b>125A</b>	2P+⊕	324	120,5	2" gas
	3P+⊕	324	120,5	2" gas
	3P+N+⊕	324	120,5	2" gas