


Part number

PHW 1665 SV



Mobile plug, PLUSO HEAVY DUTY series, 3 poles + N + PE, 6 h (red), 16 A, 380 ÷ 415 V, straight

Product description		Material properties	
Product type	Plug Mobile	Colour	RAL 7012 grey, RAL 3000 red
Series	PHW...SV, PLUSO HEAVY DUTY	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
Connection type	Screw terminal connection	China RoHs - EFUP	50
N. of poles	3 poles + N + 	REACH SVHC substances	Yes Lead
Clock position	6	SCIP number	Ca7de37f-add8-4b77-9861-279c94903ade
Specification	Straight	Approvals / Standards	
Technical data		Reference standard	EN 60309-1 and -2
Current	16 A	General ordering information	
Voltage	380 ÷ 415 V	EAN13 code	8015747084765
IP degree of protection	IP66 / IP67	Packaging Information	
Further technical details		Packaging length	255,00 mm
Weight	190,00 g	Packaging height	195,00 mm
Operating temperature range (min, max)	-40°C ... +100°C	Packaging width	245,00 mm
		Packaging weight	1,90 kg
		Packaging volume	12,18 dm ³
		Packaging description	Carton box
		Packaging quantity	10 Pcs
		Packaging EAN code	8015747084888


Part number

PHW 1665 SV



Catalogue drawings

(16 / 32A) PHW ... SV



PHW...SV	A	B	ø min	ø max
16A 2P+⊕	129	70	7	16
3P+⊕	129	77	7	16
3P+N+⊕	129	86	8	24
32A 2P+⊕	150	92	8	24
3P+⊕	150	92	8	24
3P+N+⊕	150	100	8	24