

Part number

# PK 1665 PB5



Interlocked switched socket-outlet, PK series,  
3 poles + N + PE, 6 h (red), 16 A, 200/346 ÷  
240/415 V, E16 fuse carrier

Product description	
<b>Product type</b>	Interlocked switched socket-outlet
<b>Series</b>	PK..PB5
<b>N. of poles</b>	3 poles + N +
<b>Clock position</b>	6
<b>Specification</b>	E16 fuse carrier
Technical data	
<b>Current</b>	16 A
<b>Voltage</b>	200/346 ÷ 240/415 V
<b>IP degree of protection</b>	IP55
Further technical details	
<b>Weight</b>	1.600,00 g
<b>Operating temperature range (min, max)</b>	-25°C ... +40°C
<b>IK rating (impact degree of protection)</b>	IK10


Material properties	
<b>Colour</b>	RAL 7035 grey, RAL 3000 red
<b>RoHs conformity</b>	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
<b>China RoHs - EFUP</b>	50
<b>REACH SVHC substances</b>	Yes Lead
<b>SCIP number</b>	Ce861c8d-b979-403b-96d9-80aef6dc281d
Approvals / Standards	
<b>Reference standard</b>	EN 60309-1, -2 e -4
General ordering information	
<b>EAN13 code</b>	8015747080422
Packaging Information	
<b>Packaging length</b>	400,00 mm
<b>Packaging height</b>	310,00 mm
<b>Packaging width</b>	670,00 mm
<b>Packaging weight</b>	30,00 kg
<b>Packaging volume</b>	83,08 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	15 Pcs
<b>Packaging EAN code</b>	8015747080439
<b>Sub-packaging length</b>	285,00 mm
<b>Sub-packaging height</b>	130,00 mm
<b>Sub-packaging width</b>	130,00 mm
<b>Sub-packaging weight</b>	2,00 kg
<b>Sub-packaging volume</b>	4,82 dm <sup>3</sup>
<b>Sub-packaging description</b>	Carton box
<b>Sub-packaging quantity</b>	1 Pcs
<b>Sub-packaging EAN barcode</b>	8015747080446

Part number

# PK 1665 PB5



## Catalogue drawings



	<b>A</b>
<b>2P+⊕</b>	260
<b>3P+⊕</b>	260
<b>3P+N+⊕</b>	270