


Part number

PK 1673 EB



Interlocked switched socket-outlet, PK series,
2 poles + PE, 7 h (black), 16 A, 480 ÷ 500 V,
without fuse-carrier

| Product description | |
|---|---|
| Product type | Interlocked switched socket-outlet |
| Series | PK..EB |
| N. of poles | 2 poles +  |
| Clock position | 7 |
| Cable entry | Pg16 |
| Specification | Without fuse-carrier |
| Technical data | |
| Current | 16 A |
| Voltage | 480 ÷ 500 V |
| IP degree of protection | IP44 |
| Further technical details | |
| Weight | 496,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| IK rating (impact degree of protection) | IK10 |


| Material properties | |
|------------------------------|--|
| Colour | RAL 7035 grey, RAL 9005 black |
| RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| China RoHs - EFUP | 50 |
| REACH SVHC substances | Yes Lead |
| SCIP number | Ce861c8d-b979-403b-96d9-80aef6dc281d |
| Approvals / Standards | |
| Reference standard | EN 60309-1, -2 e -4 |
| General ordering information | |
| EAN13 code | 8015747080484 |
| Packaging Information | |
| Sub-packaging weight | 0,50 kg |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747080491 |

Part number

PK 1673 EB



Catalogue drawings



| | A |
|---------------|----------|
| 2P+⊕ | 182 |
| 3P+⊕ | 182 |
| 3P+N+⊕ | 187 |