

Part number

RCF2D 0.7



Female crimp contact, RC series, 16 A, turned gold plated, wire cross section 0,75 mm², AWG 18, HNM - High Number of Matings version


| Product description | | Material properties | |
|------------------------------------|--------------------------------------|----------------------------------|--------------------------------------------------------------------------------|
| Product type | Crimp contact | RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| Series | RC | China RoHs - EFUP | 50 |
| Gender | Female | REACH SVHC substances | Yes Lead |
| Specification | HNM - High Number of Matings version | SCIP number | C0979fba-9907-458f-a94a-db781440f273 |
| Technical data | | Approvals / Standards | |
| Current | 16 A | UL | ECBT2 |
| Wire cross-section | 0,75 mm ² | cUL | ECBT8 |
| AWG size | 18 | General ordering information | |
| Contact type | Turned gold plated | EAN13 code | 8015747235174 |
| Further technical details | | eCl@ss 8.1 | 27440204 |
| Weight | 1,60 g | ETIM 7.0 | EC000796 |
| Conductors stripping length | 7,5 mm | Packaging Information | |
| | | Packaging length | 112,00 mm |
| | | Packaging height | 95,00 mm |
| | | Packaging width | 117,00 mm |
| | | Packaging weight | 0,82 kg |
| | | Packaging volume | 1,24 dm ³ |
| | | Packaging description | Carton box |
| | | Packaging quantity | 400 Pcs |
| | | Packaging EAN code | 8015747269674 |
| | | Sub-packaging length | 50,00 mm |
| | | Sub-packaging height | 44,00 mm |
| | | Sub-packaging width | 50,00 mm |
| | | Sub-packaging weight | 0,10 kg |
| | | Sub-packaging volume | 0,11 dm ³ |
| | | Sub-packaging description | Plastic box |
| | | Sub-packaging quantity | 50 Pcs |
| | | Sub-packaging EAN barcode | 8015747269681 |

Part number

RCF2D 0.7



Catalogue drawings



RCF2D contacts

| conductor section mm ² | conductor slot ø A (mm) | conductors stripping length mm |
|--------------------------------------|----------------------------|-----------------------------------|
| 0,14-0,37 | 0,9 | 7,5 |
| 0,5 | 1,1 | 7,5 |
| 0,75 | 1,3 | 7,5 |
| 1,0 | 1,45 | 7,5 |
| 1,5 | 1,8 | 7,5 |
| 2,5 | 2,2 | 7,5 |
| 3 | 2,55 | 7,5 |
| 4 | 2,85 | 7,5 |