


Part number

# SQ 1624



Interlocked switched socket-outlet, SQ series,  
3 poles + PE, 2 h (green), 16 A, > 50 V,  
without fuse-carrier

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | SQ  |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 2   |
| <b>Specification</b>  | Without fuse-carrier  |

#### Technical data

|                                |        |
|--------------------------------|--------|
| <b>Current</b>                 | 16 A   |
| <b>Voltage</b>                 | > 50 V |
| <b>IP degree of protection</b> | IP44   |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK08            |

#### Material properties

|               |                               |
|---------------|-------------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 6017 green |
|---------------|-------------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747159289 |
|-------------------|---------------|

Part number

# SQ 1624



## Catalogue drawings



| SQ  |        | A  |
|-----|--------|----|
| 16A | 2P+⊕   | 59 |
|     | 3P+⊕   | 63 |
|     | 3P+N+⊕ | 63 |

