


Part number

# SQE 1634



Interlocked switched socket-outlet, SQE series, 3 poles + PE, 3 h (red), 16 A, 380 ÷ 380 V, without fuse-carrier

#### Product description

|                       |   |
|-----------------------|---|
| <b>Product type</b>   | Interlocked switched socket-outlet  |
| <b>Series</b>         | SQE   |
| <b>N. of poles</b>    | 3 poles +  |
| <b>Clock position</b> | 3   |
| <b>Specification</b>  | Without fuse-carrier  |

#### Technical data

|                                |                           |
|--------------------------------|---------------------------|
| <b>Current</b>                 | 16 A                      |
| <b>Voltage</b>                 | 380V (50Hz.) 440V (60Hz.) |
| <b>IP degree of protection</b> | IP44                      |

#### Further technical details

|  |                 |
|--|-----------------|
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C |
| <b>IK rating (impact degree of protection)</b> | IK08            |

#### Material properties

|               |                             |
|---------------|-----------------------------|
| <b>Colour</b> | RAL 7035 grey, RAL 3000 red |
|---------------|-----------------------------|

#### Approvals / Standards

|                           |                     |
|---------------------------|---------------------|
| <b>Reference standard</b> | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

#### General ordering information

|                   |               |
|-------------------|---------------|
| <b>EAN13 code</b> | 8015747159852 |
|-------------------|---------------|

Part number

# SQE 1634



Catalogue drawings



Catalogue drawings



| SQE |        | A  |
|-----|--------|----|
| 16A | 2P+⊕   | 64 |
|     | 3P+⊕   | 65 |
|     | 3P+N+⊕ | 67 |