


Part number

TM 1675 IR



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 7 h (black), 16 A, 277/480 ÷ 288/500 V, with compartment for modular units, 4,5 DIN-rail modules EN 60715, with base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..IR/KIR |
| N. of poles | 3 poles + N +  |
| Clock position | 7 |
| Specification | With compartment for modular units, 4,5 DIN-rail modules EN 60715 With base box |

Technical data

| | |
|--------------------------------|---------------------|
| Current | 16 A |
| Voltage | 277/480 ÷ 288/500 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.410,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|-------------------------------|
| Colour | RAL 7012 grey, RAL 9005 black |
|---------------|-------------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747090353 |
|-------------------|---------------|

Packaging Information

| | |
|----------------------------------|---------------|
| Sub-packaging weight | 1,41 kg |
| Sub-packaging description | Carton box |
| Sub-packaging quantity | 1 Pcs |
| Sub-packaging EAN barcode | 8015747107051 |

Part number

TM 1675 IR



Catalogue drawings



| | A | B |
|----------------|-----|-----|
| 2P+ \oplus | 133 | 276 |
| 3P+ \oplus | 135 | 276 |
| 3P+N+ \oplus | 140 | 277 |