


Part number

TM 3224 IT



Interlocked switched socket-outlet, TM series,
3 poles + PE, 2 h (green), 32 A, > 50 V, E33 -
DIII fuse carrier, with base box

Product description		Material properties	
Product type	Interlocked switched socket-outlet	Colour	RAL 7012 grey, RAL 6017 green
Series	TM.. IT	RoHs conformity	Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight
N. of poles	3 poles + 	China RoHs - EFUP	50
Clock position	2	REACH SVHC substances	Yes Lead
Specification	E33 - DIII fuse carrier With base box	SCIP number	F6799547-ab84-42f2-938f-233ba663766d
Technical data		Approvals / Standards	
Current	32 A	Reference standard	EN 60309-1, -2 e -4
Voltage	> 50 V	General ordering information	
IP degree of protection	IP66 / IP67	EAN13 code	8015747162395
Further technical details		Packaging Information	
Weight	3.390,00 g	Sub-packaging length	150,00 mm
Operating temperature range (min, max)	-25°C ... +40°C	Sub-packaging height	188,00 mm
UL 94 flammability rating	V-2	Sub-packaging width	430,00 mm
IK rating (impact degree of protection)	IK10	Sub-packaging weight	3,39 kg
		Sub-packaging volume	12,13 dm ³
		Sub-packaging description	Carton box
		Sub-packaging quantity	1 Pcs
		Sub-packaging EAN barcode	8015747095044

Part number

TM 3224 IT



Catalogue drawings



	A
2P+⊕	162
3P+⊕	162
3P+N+⊕	169