


Part number

# TM 3244 IT



Interlocked switched socket-outlet, TM series, 3 poles + PE, 4 h (yellow), 32 A, 100 ÷ 130 V, E33 - DIII fuse carrier, with base box

|  |   |                                     |  |
|--|---|-------------------------------------|--|
| <b>Product description</b>                     |   | <b>Material properties</b>          |  |
| <b>Product type</b>                            | Interlocked switched socket-outlet  | <b>Colour</b>                       | RAL 7012 grey, RAL 1021 yellow   |
| <b>Series</b>                                  | TM.. IT   |                                     | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| <b>N. of poles</b>                             | 3 poles +  | <b>RoHs conformity</b>              |  |
| <b>Clock position</b>                          | 4   | <b>China RoHs - EFUP</b>            | 50   |
| <b>Size</b>                                    | 145 x 565 x 18 mm   | <b>REACH SVHC substances</b>        | Yes<br>Lead  |
| <b>Specification</b>                           | E33 - DIII fuse carrier<br>With base box  | <b>SCIP number</b>                  | F6799547-ab84-42f2-938f-233ba663766d   |
| <b>Technical data</b>                          |   | <b>Approvals / Standards</b>        |  |
| <b>Current</b>                                 | 32 A  | <b>Reference standard</b>           | EN 60309-1, -2 e -4  |
| <b>Voltage</b>                                 | 100 ÷ 130 V   | <b>General ordering information</b> |  |
| <b>IP degree of protection</b>                 | IP66 / IP67   | <b>EAN13 code</b>                   | 8015747091787  |
| <b>Further technical details</b>               |   | <b>Packaging Information</b>        |  |
| <b>Weight</b>                                  | 3.390,00 g  | <b>Sub-packaging length</b>         | 150,00 mm  |
| <b>Operating temperature range (min, max)</b>  | -25°C ... +40°C   | <b>Sub-packaging height</b>         | 188,00 mm  |
| <b>UL 94 flammability rating</b>               | V-2   | <b>Sub-packaging width</b>          | 430,00 mm  |
| <b>IK rating (impact degree of protection)</b> | IK10  | <b>Sub-packaging weight</b>         | 3,39 kg  |
|  |   | <b>Sub-packaging volume</b>         | 12,13 dm <sup>3</sup>  |
|  |   | <b>Sub-packaging description</b>    | Carton box   |
|  |   | <b>Sub-packaging quantity</b>       | 1 Pcs  |
|  |   | <b>Sub-packaging EAN barcode</b>    | 8015747107488  |

Part number

# TM 3244 IT



Catalogue drawings



|               | <b>A</b> |
|---------------|----------|
| <b>2P+⊕</b>   | 162      |
| <b>3P+⊕</b>   | 162      |
| <b>3P+N+⊕</b> | 169      |