


Part number

TM 3245KSSP



Interlocked switched socket-outlet, TM series, 3 poles + N + PE, 4 h (yellow), 32 A, 57/100 ÷ 75/130 V, without fuse-carrier, without base box

Product description

| | |
|-----------------------|---|
| Product type | Interlocked switched socket-outlet |
| Series | TM..SSP/KSSP |
| N. of poles | 3 poles + N +  |
| Clock position | 4 |
| Size | 114 x 255 mm fixing distance, for assembly in single or multiple boxes |
| Specification | Without fuse-carrier Without base box |

Technical data

| | |
|--------------------------------|-------------------|
| Current | 32 A |
| Voltage | 57/100 ÷ 75/130 V |
| IP degree of protection | IP66 / IP67 |

Further technical details

| | |
|--|-----------------|
| Weight | 1.190,00 g |
| Operating temperature range (min, max) | -25°C ... +40°C |
| UL 94 flammability rating | V-2 |
| IK rating (impact degree of protection) | IK10 |

Material properties

| | |
|---------------|--------------------------------|
| Colour | RAL 7012 grey, RAL 1021 yellow |
|---------------|--------------------------------|

Approvals / Standards

| | |
|---------------------------|---------------------|
| Reference standard | EN 60309-1, -2 e -4 |
|---------------------------|---------------------|

General ordering information

| | |
|-------------------|---------------|
| EAN13 code | 8015747126595 |
|-------------------|---------------|