


Part number

TM 6343 IR



Interlocked switched socket-outlet, TM series, 2 poles + PE, 4 h (yellow), 63 A, 100 ÷ 130 V, with compartment for modular units, 6 DIN-rail modules EN 60715, with base box

| | | | |
|--|---|-------------------------------------|--|
| Product description | | Material properties | |
| Product type | Interlocked switched socket-outlet | Colour | RAL 7012 grey, RAL 1021 yellow |
| Series | TM..IR/KIR | RoHs conformity | Compliant with exemption 6(c): copper alloy containing up to 4% lead by weight |
| N. of poles | 2 poles +  | China RoHs - EFUP | 50 |
| Clock position | 4 | REACH SVHC substances | Yes Lead |
| Size | 145 x 565 x 18 mm | SCIP number | F6799547-ab84-42f2-938f-233ba663766d |
| Specification | With compartment for modular units, 6 DIN-rail modules EN 60715 With base box | Approvals / Standards | |
| Technical data | | Reference standard | EN 60309-1, -2 e -4 |
| Current | 63 A | General ordering information | |
| Voltage | 100 ÷ 130 V | EAN13 code | 8015747092364 |
| IP degree of protection | IP66 / IP67 | Packaging Information | |
| Further technical details | | Sub-packaging length | 150,00 mm |
| Weight | 3.135,00 g | Sub-packaging height | 188,00 mm |
| Operating temperature range (min, max) | -25°C ... +40°C | Sub-packaging width | 430,00 mm |
| UL 94 flammability rating | V-0 (insert), V-2 (enclosure) | Sub-packaging weight | 3,14 kg |
| IK rating (impact degree of protection) | IK10 | Sub-packaging volume | 12,13 dm ³ |
| | | Sub-packaging description | Carton box |
| | | Sub-packaging quantity | 1 Pcs |
| | | Sub-packaging EAN barcode | 8015747108799 |

Part number

TM 6343 IR



Catalogue drawings

