

Part number

# CC 0.7 AN



Male crimp contact, CC series, 16 A, turned silver plated, wire cross section 0,75 mm<sup>2</sup>, AWG 18, advanced opening

| Product description                |                      | Material properties              |   |
|------------------------------------|----------------------|----------------------------------|---|
| <b>Product type</b>                | Crimp contact        | <b>Main material</b>             | Copper alloy  |
| <b>Series</b>                      | CC                   |                                  | Compliant with exemption                              |
| <b>Gender</b>                      | Male                 | <b>RoHs conformity</b>           | 6(c): copper alloy containing up to 4% lead by weight |
| <b>Specification</b>               | Advanced opening     | <b>China RoHs - EFUP</b>         | 50  |
| Technical data                     |                      | <b>REACH SVHC substances</b>     | Yes<br>Lead   |
| <b>Current</b>                     | 16 A                 | <b>SCIP number</b>               | C0979fba-9907-458f-a94a-db781440f273                  |
| <b>Wire cross-section</b>          | 0,75 mm <sup>2</sup> | Approvals / Standards            |   |
| <b>AWG size</b>                    | 18                   | <b>Certifications</b>            | CSA, EAC  |
| <b>Contact type</b>                | Turned silver plated | <b>UL</b>                        | ECBT2   |
| Further technical details          |                      | General ordering information     |   |
| <b>Weight</b>                      | 1,00 g               | <b>EAN13 code</b>                | 8015747011198   |
| <b>Conductors stripping length</b> | 7,5 mm               | <b>eCl@ss 8.1</b>                | 27440204  |
|                                    |                      | <b>ETIM 7.0</b>                  | EC000796  |
|                                    |                      | Packaging Information            |   |
|                                    |                      | <b>Sub-packaging length</b>      | 50,00 mm  |
|                                    |                      | <b>Sub-packaging height</b>      | 44,00 mm  |
|                                    |                      | <b>Sub-packaging width</b>       | 50,00 mm  |
|                                    |                      | <b>Sub-packaging weight</b>      | 0,05 kg   |
|                                    |                      | <b>Sub-packaging volume</b>      | 0,11 dm <sup>3</sup>                                  |
|                                    |                      | <b>Sub-packaging description</b> | Plastic box   |
|                                    |                      | <b>Sub-packaging quantity</b>    | 50 Pcs  |
|                                    |                      | <b>Sub-packaging EAN barcode</b> | 8015747011204   |

Part number

# CC 0.7 AN



## Catalogue drawings



### CCF, CCM and CC..AN contacts

| conductor section<br>mm <sup>2</sup> | conductor slot<br>$\varnothing A$ (mm) | conductors stripping length<br>(mm) |
|--------------------------------------|--|-------------------------------------|
| 0,14-0,37                            | 0,9                                    | 7,5                                 |
| 0,5                                  | 1,1                                    | 7,5                                 |
| 0,75                                 | 1,3                                    | 7,5                                 |
| 1,0                                  | 1,45                                   | 7,5                                 |
| 1,5                                  | 1,8                                    | 7,5                                 |
| 2,5                                  | 2,2                                    | 7,5                                 |
| 3                                    | 2,55                                   | 7,5                                 |
| 4                                    | 2,85                                   | 7,5                                 |