

Part number

CCMJD 2.5



Male crimp contact, CC series, 16 A, turned gold plated, wire cross section 2,5 mm², AWG 14, basic gold plating


Product description		Material properties	
Product type	Crimp contact	Main material	Copper alloy
Series	CC		Compliant with exemption
Gender	Male	RoHs conformity	6(c): copper alloy containing up to 4% lead by weight
Specification	Basic gold plating	China RoHs - EFUP	50
Technical data		REACH SVHC substances	Yes Lead
Current	16 A	SCIP number	C0979fba-9907-458f-a94a-db781440f273
Wire cross-section	2,50 mm ²	Approvals / Standards	
AWG size	14	Certifications	CSA, EAC
Contact type	Turned gold plated	UL	ECBT2
Further technical details		General ordering information	
Weight	1,35 g	EAN13 code	8015747076678
Conductors stripping length	7,5 mm	eCl@ss 8.1	27440204
		ETIM 7.0	EC000796
		Packaging Information	
		Packaging length	112,00 mm
		Packaging height	95,00 mm
		Packaging width	117,00 mm
		Packaging weight	1,28 kg
		Packaging volume	1,24 dm ³
		Packaging description	Carton box
		Packaging quantity	800 Pcs
		Packaging EAN code	8015747207416
		Sub-packaging length	50,00 mm
		Sub-packaging height	44,00 mm
		Sub-packaging width	50,00 mm
		Sub-packaging weight	0,16 kg
		Sub-packaging volume	0,11 dm ³
		Sub-packaging description	Plastic box
		Sub-packaging quantity	100 Pcs
		Sub-packaging EAN barcode	8015747094092

Part number

CCMJD 2.5



Catalogue drawings



CCFJD and CCMJD contacts

conductor section mm ²	conductor slot $\varnothing A$ (mm)	conductors stripping length mm
0,14-0,37	0,9	7,5
0,5	1,1	7,5
0,75	1,3	7,5
1,0	1,45	7,5
1,5	1,8	7,5
2,5	2,2	7,5
3,0	2,55	7,5
4,0	2,85	7,5