

Part number

# CHIN 16



Bulkhead mounting housing, LS-TYPE series, with 2 levers, size "77.27"

#### Product description

<b>Product type</b>	Bulkhead mounting housing
<b>Series</b>	LS-TYPE
<b>Closing type</b>	With 2 levers
<b>Size</b>	Size 77.27
<b>Cable entry</b>	Without cable entry

#### Technical data

<b>IP degree of protection</b>	IP65
--------------------------------	------

#### Further technical details

<b>Weight</b>	95,00 g
<b>Operating temperature range (min, max)</b>	-40°C...+125°C

#### Material properties

<b>Other materials</b>	Lever: Polyamide (PA) Gasket: NBR
<b>Colour</b>	RAL 9005 black
<b>RoHs conformity</b>	Compliant
<b>China RoHs - EFUP</b>	E
<b>REACH SVHC substances</b>	No

#### Approvals / Standards

<b>Certifications</b>	DNV, BV
<b>UL</b>	ECBT2
<b>cUL</b>	ECBT8

#### General ordering information

<b>EAN13 code</b>	8015747163095
<b>eCl@ss 8.1</b>	27440202
<b>ETIM 7.0</b>	EC000437


#### Packaging Information

<b>Packaging length</b>	360,00 mm
<b>Packaging height</b>	165,00 mm
<b>Packaging width</b>	315,00 mm
<b>Packaging weight</b>	3,80 kg
<b>Packaging volume</b>	18,71 dm <sup>3</sup>
<b>Packaging description</b>	Carton box
<b>Packaging quantity</b>	40 Pcs
<b>Packaging EAN code</b>	8015747187602
<b>Sub-packaging weight</b>	0,48 kg
<b>Sub-packaging description</b>	Plastic packaging
<b>Sub-packaging quantity</b>	5 Pcs
<b>Sub-packaging EAN barcode</b>	8015747187619

# Part number CHIN 16



Catalogue drawings



Catalogue drawings

**CH..N - MA, MF..N enclosures** size "77.27" **LS-TYPE version**

inserts:	page	housings with double lever	hoods with 4 pegs
CD .....	40 poles + 49+52 *		
CT, CTS **)	40 poles + 56 *		
CDD .....	72 poles + 62+65 *		
CDE .....	32 poles + 82+84 *		
CSH .....	16 poles + 90+92 *		
CCE .....	16 poles + 98+102 *		
CNE, CSE, JCNE, JCSE	16 poles + 99 and 108 *		
CSS .....	16 poles + 120+122 *		
CTE, CTSE **)	16 poles + 128 *		
CMSE .....	6+2 (aux) poles + 137 *		
CMCE .....	6+2 (aux) poles + 136 *		
CP .....	6 poles + 149+150 *		
CX .....	6/36 e 12/2 poles + 152+153 *		
CX .....	4/0 e 4/2 poles + 154 *		
MIXO .....	4 modules 160-195 *		

insert centre distance: 77,5 x 27 mm  
\* refer to catalogue page CN.12

description	part no.	entry	part no.	entry
bulkhead mounting housing, with 2 levers	<b>CHIN 16</b>	M		
surface mounting housing, high construction, with 2 levers	<b>MAPN 16.32</b>	32		
with pegs, side entry			<b>MHON 16.32</b>	32
with pegs, side entry, high construction			<b>MFON 16.32</b>	32
with pegs, top entry			<b>MHVN 16.32</b>	32
with pegs, top entry, high construction			<b>MFVN 16.32</b>	32

\*\*) only in the CHIN 16 enclosure

panel cut-out for bulkhead mounting housing in mm

- kiln powder coating with RAL 9005 black epoxy polyester powder  
- RAL 9005 black self-extinguishing thermoplastic locking lever (spare lever page 12)

dimensions shown are not binding and may be changed without notice

dimensions in mm	dimensions in mm
<b>CHIN 16</b>	<b>MFON 16.32</b>
<b>MAPN 16.32</b>	<b>MFVN 16.32</b>
	<b>MHON 16.32</b>
	<b>MHVN 16.32</b>